

Desktop Products

# G84-4700 Compact Programmable Keypad

**Compact Keypad Featuring MX Technology  
with Gold Crosspoint Contacts**

## Main Applications

### Desktop

- Numerical input
- Control systems
- Frequent entry of numbers
- Extension for notebook computer

## Key Features

- Programmable 21-key numeric layout
- Equally suitable for left- and righthanded users
- Low space requirements
- All keys can be user-defined with up to 24 characters per key
- 4 additional user-programmable function keys, can be labeled individually
- Digits can be entered independently of the status of the Num Lock in the system (operation on notebook PC)
- Variable decimal separator [., [, ], [00], or [000]
- External standard keyboard can be connected
- Matches design of Cherry keyboards G84-4100
- Uses mechanical keys from our ML series with high-precision key action; small physical dimensions:
- Reliability: MTBF: 550,000 hours

## Main Part Numbers

### G84-4700LPBUS-0

Light grey, PS/2 interface, 21 programmable keys, 4 relegendable, ML keyswitches, second PS/2 port for keyboard

### G84-4700LPBUS-2

Black, PS/2 interface, 21 programmable keys, 4 relegendable, ML keyswitches, second PS/2 port for keyboard

### G84-4700 LUCUS-0

Light grey, USB interface, 21 programmable keys, 4 relegendable, ML keyswitches

### G84-4700 LUCUS-2

Black, USB interface, 21 programmable keys 4 relegendable, ML keyswitches

## (1) International Layouts

US Belgian/Swiss  
English (US)/English (UK)  
DE Germany  
DK Danish/Norwegian  
ES Spain  
FR France  
IT Italy  
SF Sweden/Finland

**Other versions available on request.**

Desktop Products

# G84-4700 Compact Programmable Keypad


G84-4700 PRB (1)

**Technical Data****Power Supply**  
3.3-5.0 VDC  $\pm$  10% SELV**Current Input**  
typ. 50 mA**Connecting Cable**  
approx. 1.75 m long**Weight**  
approx. 260 g**Storage Temperature**  
-20°C to 60°C**Operating Temperature**  
0°C to 50°C**Dimensions of Housing**  
90 x 132 x 36 mm**Cherry MX Switches with Gold Crosspoint Contacts****Actuation Characteristics**  
Soft contact

For information on repairs or warranty status contact:

Cherry Technical Support

Phone: 800.510.1689

E-Mail: [keyboardsupport@cherrycorp.com](mailto:keyboardsupport@cherrycorp.com)**Contact**

Call, fax or visit our website for more information.

Last Update: 10/28/08

**Cherry Electrical Products**11200 88th Avenue  
Pleasant Prairie, WI 53158Phone: 262.942.6500  
Web: [www.cherrycorp.com](http://www.cherrycorp.com)E-Mail: [sales@cherrycorp.com](mailto:sales@cherrycorp.com)  
Fax: 262.942.6566

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.