

# Accessories

## SFP (Small Form Pluggable)

### SFP (Small Form Pluggable)

#### SFP 100MM

Multi-mode 100Mbps 2KM Fiber Transceiver , commercial operating Temp. 0~ 70°C



**Wave-length:** 1310nm  
**Tx Power:**  
-20dBm(Min)~-14dBm(Max)  
**Rx Sensitivity:** -31dBm(Max)  
**Linkbudget:** 11dBm

**Operation Temperature :**  
-10°C~70°C  
**Storage Temperature:** -40°C~85°C  
**Operating Humidity:** 85%

#### SFP 100MM -w

Multi-mode 100Mbps 2KM Fiber Transceiver, wide operating Temp. -40~ 85°C



**Wave-length:** 1310nm  
**Tx Power:**  
-20dBm(Min)~-14dBm(Max)  
**Rx Sensitivity:** -31dBm(Max)  
**Linkbudget:** 11dBm

**Operation Temperature :**  
-40°C~85°C  
**Storage Temperature:** -40°C~85°C  
**Operating Humidity:** 85%

#### SFP100SM30

Single mode 100Mbps 30KM Fiber Transceiver, Commercial operating Temp. 0~ 70°C



**Wave-length:** 1310nm  
**Tx Power:**  
-15dBm(Min)~-8dBm(Max)  
**Rx Sensitivity:** -34dBm(Max)

**Linkbudget:** 19dBm  
**Operation Temperature :** 0°C~70°C  
**Storage Temperature:** -40°C~85°C  
**Operating Humidity:** 85%

#### SFP100SM30-w

Single mode 100Mbps 30Km Fiber Transceiver , Wide operating Temp. -40~ 85°C



**Wave-length:** 1310nm  
**Tx Power:**  
-15dBm(Min)~-8dBm(Max)  
**Rx Sensitivity:** -34dBm(Max)  
**Linkbudget:** 19dBm

**Operation Temperature :**  
-40°C~ 85°C  
**Storage Temperature:** -40°C~85°C  
**Operating Humidity:** 85%

## SFP (Small Form Pluggable)

### SFP (Small Form Pluggable)

#### SFPGSX

1000Base-SX multi-mode transceiver 550m , commercial operating Temp, 0~70°C



**Wave-length:** 850nm  
**Tx Power:**  
-9.5dBm(Min)~-4dBm(Max)  
**Rx Sensitivity:** -18dBm(Max)

**Linkbudget:** 8.5dBm  
**Operation Temperature :** 0°C~70°C  
**Storage Temperature:** -40°C~85°C  
**Operating Humidity:** 85%

#### SFPGSX-w

1000Base-SX multi-mode transceiver 550m , commercial operating Temp, -40~85°C



**Wave-length:** 850nm  
**Tx Power:**  
-9.5dBm(Min)~-4dBm(Max)  
**Rx Sensitivity:** -18dBm(Max)  
**Linkbudget:** 8.5dBm

**Operation Temperature :**  
-20°C~85°C  
**Storage Temperature:** -40°C~85°C  
**Operating Humidity:** 85%

#### SFPGLX10

1000Base-LX single-mode transceiver 10Km , commercial operating Temp, 0~70°C



**Wave-length:** 1310nm  
**Tx Power:**  
-9.5dBm(Min)~-3dBm(Max)  
**Rx Sensitivity:** -20dBm(Max)

**Linkbudget:** 10.5dBm  
**Operation Temperature :** 0°C~70°C  
**Storage Temperature:** -40°C~85°C  
**Operating Humidity:** 85%

#### SFPGLX10-w

1000Base-LX single-mode transceiver 10Km , commercial operating Temp, -40~85°C



**Wave-length:** 1310nm  
**Tx Power:**  
-9.5dBm(Min)~-3dBm(Max)  
**Rx Sensitivity:** -20dBm(Max)  
**Linkbudget:** 10.5dBm

**Operation Temperature :**  
-40°C~ 85°C  
**Storage Temperature:** -40°C~85°C  
**Operating Humidity:** 85%