

Specification

Network Interface

WLAN Standard: 802.11b/g WLAN

Spread Spectrum Technology:

DSSS(802.11b), OFDM(802.11g)

Tx Power: 13-17dBm at maximum radiation direction

Rx Sensitivity: -71 dBm @ 54 Mbps, -84 dBm @ 11Mbps

Transmission Rate: 54 Mbps (max.) with auto fallback (54,48, 36, 24, 18, 12, 11, 9, 6, 5.5, 2, 1 Mbps)

Transmission Distance: Up to 100 meters (open area)

Antenna: Supports the antenna diversity function

Ethernet: 1* 10/100BaseTX, Auto MDI/MDI-X

Connector: RJ-45

Protection: Built-in 1.5 KV magnetic isolation protection

Serial Communication

Number of Ports: 1

Interface: RS-232, RS422, 2/4-wire RS485

Connectors: male DB9

Baud Rates: 110 bps to 230.4K bps

Data Bits: 5, 6, 7, 8

Parity: odd, even, none

Stop Bits: 1, 1.5, 2

RS-232: TxD, RxD, RTS, CTS, DTR, DSR, GND, DCD

RS-422: Tx+,Tx-, Rx+, Rx-,GND

RS-485 (4-wire): Tx+,Tx-, Rx+, Rx-,GND

RS-485 (2-wire): Data+, Data-,GND

Flow Control: XON/XOFF, RTS/CTS, DTR/DSR

Serial Line Protection: 15KV ESD

Long Distance Termination: 2*pin 120ohm DIP switches

Features

Protocols: IP, TCP, UDP, ICMP, DHCP, BootP, ARP/RARP, SNMP, HTTPS, SSH, SNTP, SMTP,

LED:

Power 1/Power 2: Startup(Red); Ready(Green)

LAN : 10M Link(Orange), 100M Link(Green)

WLAN: Good Link Quality(Green), Poor Link Quality (Orange)

Serial: Transmitting data(Green), Receiving data(Orange)

Configuration: JetPort Commander, HTTPS, SSH

Serial Service: Virtual COM, TCP Server, TCP Client, TCP Tunnel and UDP

WLAN Discover: 5 AP list

WLAN Strength: 5 Levels

WLAN Security:

WEP 64-bit/128-bit data encryption, AES, WPA2

Reset: Software reload default, Hardware reset button

Beeper: Embedded beeper for positioning

SNTP: For time management

Access IP Table: 16 IP addresses to prevent illegal users

Monitor: Devices' status, VCOM status

E-Mail Alert:

Automatic e-mail warning by pre-defined events

System Log: Trap to Syslog server or local display

System Events: Cold/Warm Start, Login Failed, IP and Password Changed, Access IP Blocked, Serial Port DCD/RI/DSR/CTS changed, Serial Port connected/disconnected

SNMP:

RFC1213 MIB II, RFC1317 RS232_like and SNMP Trap

Windows Utility

JetPort Commander: Device Discovery, Auto IP, Network Setting(Wire and Wireless), Device and Serial Port Setting and monitoring, Notification setting, Firmware Upgrade, Configuration Backup and Restore, Group Configuration Wizards

Serial Service Mode: Virtual COM, TCP Server, TCP Client, TCP Tunnel and UDP

Advanced Serial Setting: TCP Alive Check Timeout, Inactivity Idle Timeout, Performance mode, Delimiter, Force TX Timeout for Data Packing and Force TX interval time

Group Configuration Wizard: JetPort Commander: Group IP Wizard, Group firmware upgrade, Group Backup/Restore, VCOM and TCP Tunnel Setup Wizard

Power Requirements

System Power:

PWR1: 12~48VDC Terminal Block

PWR2: 12~48VDC Power Jack with Power Adapter

Power Line protection:

1 KV Burst (EFT), EN61000-4-4

0.5 KV Surge, EN61000-4-5

Mechanical

Dimensions: 96.1mm(W)x124mm(D)x29.6mm(H)

Regulatory Approvals:

FCC Class A, CE Class A, UL, RoHS

Environmental

Operating Temperature: -10 ~ 55°C

Operating Humidity: 5% ~ 95%, (non-condensing)

Storage Temperature: -20 ~ 70°C

Warranty: 3 years

Ordering Information

JetPort 5801 1-port RS-232/422/485 Wireless Serial Device Server

Includes:

- 1-port RS-232/422/485 Wireless Serial Device Server with Antenna
- Quick Installation Guide
- 100~240VAC power adapter
- Din-Rail kit and foot pads
- Documentation and Software CD-ROM