Nylon Hose Clamps





Features:

- The plastic clip is an injection moulded multi-purpose clip and provides an alternative method of clamping hoses.
- · Material: UV and heat stabilised nylon 66.





Characteristics:

The moulded plastic one-piece hose clip is easy to use and produces high integrity clamping with its double row of interlocking teeth. It can be fitted after the hose is connected and is secured by tightening the jaws of the clip to the required tension. The first teeth of the clip can be engaged by hand, followed by adjustable pliers or multi-grips until at least 3 teeth are interlocked. The clip may be released by twisting sideways to disengage the teeth. Again, pliers are quite suitable for this purposes.

The "Herbie Clip" is capable of withstanding up to 200psi on leakage tests over a temperature range <0° through to 105°C. It is non corrosive under atmospheric conditions and is highly resistant to most chemicals. For high volume usage, special manual and pneumatic tools have been designed and are available on application.

Specifications

Adjustment Range	Clamp Ident	3 Teeth Engaged (A)	Band Thickness (E)	Band Width	Part Number
7.9 - 9.6	В	9.2	1.6	4.4	7235318
9.2 - 10.8	BB	10.3	1.7	4.5	7235320
11.1 - 13.4	CC	12.9		6.1	7235343
12.0 - 14.5	D	13.8			7235355
13.1 - 15.7	Е	15.1	2.0	7.2	7235367
16.9 - 19.8	G	19.1	2.1	6.9	7235380
20.3 - 23.7	J	23.0		6.4	7235409
24.5 - 28.4	L	27.6		7.1	7235422
26.5 - 30.4	М	29.5	2.2	7.4	7235434
28.8 - 33.0	N	32.2	2.0	9.0	7235446

Dimensions : Millimetres

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell pic 2009.

http://www.farnell.com http://www.newark.com http://www.cpc.co.uk

