


Countersunk head self tapping screws - PoziDriv® - Pointed



DIN 7982 C Z
ISO 7050 C Z
BS 4174 AB

Materials and Finishes

Case hardened steel/Zinc & clear de-embrittled
Stainless steel/Self colour

Dimensions

d	2.2	2.9	3.5	3.9	4.2	4.8	5.5	6.3
d	No.2	No.4	No.6	-	No.8	No.10	No.12	No.14
D max	4.3	5.5	6.8	7.5	8.1	9.5	10.8	12.4
H max	1.3	1.7	2.1	2.3	2.5	3	3.4	3.8
Recess No.	1	1	2	2	2	2	3	3

Preferred Lengths

		Thread (d)							
		2.2	2.9	3.5	3.9	4.2	4.8	5.5	6.3
Length (L)	4.5	ST	ST						
	6.4	ST	ST A2	ST					
	7.9	ST	ST A2	ST					
	9.5	ST	ST A2	ST A2	ST	ST A2			
	12.7	ST	ST A2	ST A2	ST	ST A2	ST A2	ST	
	15.9	ST	ST A2	ST A2	ST	ST A2	ST A2	ST	
	19		ST A2	ST A2	ST	ST A2	ST A2	ST	ST
	22.2		ST	ST	ST	ST	ST		
	25.4		ST A2	ST A2	ST	ST A2	ST A2	ST	ST
	31.8			ST	ST	ST A2	ST A2	ST	ST
	38			ST	ST	ST A2	ST A2	ST	ST
	44.5					ST A2	ST A2	ST	ST
	50.8					ST A2	ST A2	ST	ST
	57						ST	ST	
63						ST	ST	ST	

	70								
	75						ST	ST	ST

ST - Steel, Zinc & clear de-embrittled
A2 - Stainless steel