



ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

REVISIONS			DOC. NO. SPC-F004 * Effective: 12/21/98 * DCP No: 680					
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1963	A	RELEASED	JN	10/08/08	JWM	10/08/08	JWM	10/08/08



Description:

- Standoff
- Body Diameter:0.25"
- Body Plating:Zinc
- Spacer Material:Brass
- Spacer Style:Round
- Spacer Thread Type:Male / Male
- Spacing Height:0.5"

Mfg. p/n	L Length	S	P	D Diameter	T Thread
SPC21612	.500 (12.2)	.250 (6.4)	.250 (6.4)	.187 (4.7)	4-40
SPC21613		.312 (7.9)		.250 (6.4)	6-32
SPC21614		.312 (7.9)		.250 (6.4)	8-32

SPC-F004.DWG

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.



SPC TECHNOLOGY

TOLERANCES UNLESS OTHERWISE SPECIFIED DECIMAL .XXX ± .005[0.15]	DRAWN BY:	DATE:	DRAWING TITLE:			
	Jaosn Nash	10/08/08	MALE/MALE, HINGE STANDOFF			
	CHECKED BY:	DATE:	SIZE	DWG. NO.	ELECTRONIC FILE	REV
	JWM	10/08/08	A	Ta-1214	Ta-1214.DWG	A
APPROVED BY:	DATE:	SCALE: NTS		U.O.M.: INCHES [mm]		
JWM	10/08/08			SHEET: 1 OF 1		