




ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART, CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS

DOC. NO. SPC-F005 \* Effective: 7/8/08 \* DCP No: 1398

| DCP # | REV  | DESCRIPTION | DRAWN | DATE     | CHECKD | DATE     | APPRV | DATE     |
|-------|------|-------------|-------|----------|--------|----------|-------|----------|
| XX    | XX   | XXXX        | XXXX  | 06-10-08 | XXXX   | 06-10-08 | XXXX  | 06-10-08 |
| XXXX  | XXXX |             | XXXX  | 06-10-08 | XXXX   | 06-10-08 | XXXX  | 06-10-08 |



**Key Specifications/Special Features:**

- Type : Condenser
- Directivity : Super cardioid
- Impedance : 130 ohms ± 20%
- Frequency response : 50Hz to 18kHz
- Sensitivity : -70dB ±3dB at 1kHz (0dB = 1V/g bar)
- Output : Balance
- Standard operating voltage : DC 48V
- Weight : 220g ±10g (with cable)



DISCLAIMER:  
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

|              |          |
|--------------|----------|
| DRAWN BY:    | DATE:    |
| XXXX         | 06-10-08 |
| CHECKED BY:  | DATE:    |
| XXXX         | 06-10-08 |
| APPROVED BY: | DATE:    |
| XXXX         | 06-10-08 |

DRAWING TITLE:

Condenser Microphone

|            |                     |                 |      |
|------------|---------------------|-----------------|------|
| SIZE       | DWG. NO.            | ELECTRONIC FILE | REV  |
| A          | CT-03               | 01P0752         | XX   |
| SCALE: NTS | U.O.M.: INCHES [mm] | SHEET: 1        | OF 1 |