

RBB Series



- RBB-04A2-PS
 - RBB-04B2-PS
 - RBB-04C2-PS
 - RBB-04D2-PS
 - RBB-04F-PS
- Balanced Armature Receiver
 - Extremely Compact Size
 - High Fidelity Sound Reproduction
 - Great for in-ear headphones

Specifications:

| Model Name | RBB-04A2-PS | RBB-04B2-PS | RBB-04C2-PS | RBB-04D2-PS | RBB-04F-PS |
|---------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Spout | No | No | Yes | No | Yes |
| Sensitivity* | 104 ± 2 dB | 102.5 ± 3 dB | 104 ± 2 dB | 101 ± 2 dB | 98 ± 2 dB |
| Total Harmonic Distortion | 10% Max | 10% Max | 10% Max | 10% Max | 10% Max |
| Impedance | 400 ± 80 Ω | 33 ± 7 Ω | 400 ± 80 Ω | 15.5 ± 1.8 Ω | 33 ± 7 Ω |
| DC Resistance | 236 ± 24 Ω | 30 ± 4.5 Ω | 236 ± 24 Ω | 12.8 ± 1.5 Ω | 30 ± 4.5 Ω |
| Externals Size | 4.3 × 5.6 × H2.8mm | 4.3 × 5.6 × H2.8mm | 4.3 × 5.6 × H2.8mm | 4.3 × 5.6 × H2.8mm | 4.3 × 5.6 × H2.8mm |
| Weight | 0.2 g | 0.2 g | 0.2 g | 0.2 g | 0.2 g |

* 1kHz, 0.5W input power, 2cc coupler [HA-1]

