

Locks and inserts

Operating handle delivered with the enclosure.

- It can be attached to the locking system by means of a fixing element.
- It can also be used to loosen the caps protecting the studs when painting.



Standard locks

Spacial S3D wall-mounting enclosures are supplied with a 3-mm double-bar lock as standard.

- Spare lock: order ref. **NSYAEDLS3DRL** (escutcheon + cam + washer).
- Large range of standardised inserts covering all the most common needs.
- Installation and removal with a single screw.



Description	Reference of form insert*
6-mm square	NSYAEDLS6S3D
7-mm square	NSYAEDLS7S3D
8-mm square	NSYAEDLS8S3D
3-mm double bar	NSYAEDLB3S3D
5-mm double bar	NSYAEDLB5S3D
CNOMO 6.5-mm triangular	NSYAEDLT6S3D
8-mm triangular	NSYAEDLT8S3D

* Delivered with 1 plastic key.

Standard handles with keys

Attractive and ergonomic bi-material handle.

- Large range of barrels covering all the most common needs.
- Standard cam (see diagram above).
- The installation of the standard handle does not require the escutcheon to be removed.



Description	Reference of handle with keys*
1242	NSYAEDL1242S3D
405	NSYAEDL405S3D
421	NSYAEDL421S3D
455	NSYAEDL455S3D
2331A	NSYAEDL2331S3D
2433A	NSYAEDL2433S3D
3113A	NSYAEDL3113S3D

* Delivered with 2 keys.