Safety Padlocks



Brady Safety Padlocks

Color	1 Padlock/Package	6 Padlocks/Package
	Catalog No.	Catalog No.
Red	99552	51339
Blue	99556	51344
Green	99564	51345
Yellow	99570	51346
Orange	99576	51347
Black	99580	51353
Brown	101958	101956
Purple	104919	104916



NEW!

Brady Keyed Alike Safety Padlocks

3 Padlock/Package	6 Padlocks/Package	Color
Catalog No.	Catalog No.	
105886	105890	Red
105887	105891	Blue
105899	105893	Green
105888	105892	Yellow

When keyed alike, all locks in a set can be opened with the same key. This option is beneficial when multiple locks are assigned to a single employee.



Safety Padlock Labels

outoty i dulook Edbolo			
Catalog No.	Description		
51379	English (6/Pkg)		
51384	Spanish (6/Pkg)		
51385	French (6/Pkg)		

The Ultimate Lockout Lock!

The Brady Safety Padlock complies with all OSHA requirements and is a safer alternative to metal locks for lockout applications. The body is nonconductive, while the unique key cylinder prevents electricity from traveling from the shackle to the key, further protecting workers from shock.

The Brady Safety Padlock also delivers superior corrosion resistance. Third-party tests confirm that Brady outperforms the leading competitor when subjected to repeated salt water sprays. For more information, go to www.bradyid.com/lockout.

Features & Benefits

- Compact and lightweight
- · One-piece "seamless" body construction for rugged durability
- Special 6-pin cylinder resists tampering and offers more unique key cuts
- Key-retaining safety feature prevents key from being removed until shackle is securely closed.
- Ribbed sides for secure gripping, even when wearing gloves
- "Danger" and "Property Of" labels provided in English, Spanish and French
- Locks come keyed different or in keyed-alike sets. Custom keying and charting also available (see pg 392)
- · Lock bodies can be custom laser engraved upon request.
- Available in 8 high-visibility colors
- One key supplied standard with each padlock
- · Sold individually and in 6-packs

Product Specifications

- Fiberglass reinforced nylon body for extra impact resistance
- Triple-coated hardened steel shackle resists corrosion
- Reserved paracentric keyway provides optimal security
- Service temperature: 0° 250° F (-20° 120° C)
- Lock body dimensions: 13/4"H x 11/2"W x 4/5"D

