



REVISIONS

DOC. NO. SPC-F004 \* Effective: 7/8/02 \* DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1453	A	RELEASED	JWM	10/4/02	HO	2/10/04	CG	2/17/04



**Electrical Specifications**

Accuracies are ±(% of reading + number of least significant digits) at 23°C ±5°C <75% R.H.

	Range	Resolution	Accuracy	Input Impedance	
DC Voltage	4V	1mV	±(0.8%+1)	10 Megohms	Response Time: 2 sec. Max.
	40V	10mV			
	600V	1V			
	Range	Resolution	Accuracy	Frequency (Hz)	
AC Voltage	4V	1mV	±(1.2%+3)	40 ~ 400	Input Impedance: 10 Megohms Response Time: 2 sec. Max.
	40V	10mV			
	600V	1V			
	Range	Resolution	Accuracy	Input Resistor	
DC Current	40 ~ 400mA	100µA	±(1.2%+3)	1 Ohm	Max. Input Current: 400mA Protected by: 400mA fuse
	Range	Resolution	Accuracy	Input Resistor	
AC Current	40 ~ 400mA	100µA	±(1.2%+5)	1 Ohm	Max. Input Current: 400mA Protected by: 400mA fuse
	Range	Resolution	Accuracy	Measurement Voltage/Current	
Resistance	400 Ohms	100 milliohms	±(1.0%+2)	VDDA 1.2mA or Less	Response Time: 5 sec. Max on 40 Megohm range. 2 sec. On all other ranges Temp Range for 40 Megohm 18°C to 30°C
	4K Ohms	1 Ohm		0.7V (Typ)	
	40K Ohms	10 Ohms		0.7mA or less	
	400K Ohms	100 Ohms		0.47V (Typ) 0.47mA or less	
	4 Megohms	1K Ohms			
	40 Megohms	10K Ohms			±(1.5%+2)

**Features:**

- Compact size and easy operation
- Ergonomic design for better hand gripping
- Fully automatic and extreme low power consumption
- Auto-polarity with engineering units annunciator
- Auto-voltage range selection:DCV & ACV:1mV~600V
- Auto-ampere range selection: DCA & ACA: 40mA~400mA
- Auto-resistance range selection:0.1 ohm ~ 40Megohms
- Continuity Test
- Auto-power off
- Data Hold

**General Specifications**

- Display: 3<sup>3</sup>/<sub>4</sub> digit LCD, 3999 counts with decimal point and engineering units annunciator display
- Polarity: Automatic (-) negative polarity indication
- Zero Adjust: Automatic
- Measuring Method: Dual slope integration A to D converter system
- Over Range Indication: Only the "OL" is displayed
- Power: Single, standard 9 volt battery (NEDA 1604, JIS 006P or (IEC6F22)
- Dimension: 232mm(L) x 45mm(w) x 31mm(D)
- Weight: Approx. 160gm including battery
- Includes: Battery and alligator clip
- Designed for indoor use at temperature of 5°C to 40°C and altitude up to 2,000m.

SPC-F004.DWG

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	DRAWN BY:	DATE:	DRAWING TITLE:			
	Jeff McVicker	10/4/02	Pen Digital Multimeter with Logic Function			
	CHECKED BY:	DATE:	SIZE	DWG. NO.	ELECTRONIC FILE	REV
	Hisham Odish	2/10/04	A	72-6620	66F3571.dwg	A
APPROVED BY:	DATE:	SCALE: NTS		U.O.M.: INCHES [mm]		SHEET: 1 OF 1
Chris Gloger	2/17/04					

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.