



REVISIONS

DOC. NO. SPC-F004 * Effective: 7/8/02 * DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1740	A	RELEASED	JWM	9/20/04	SF	9/20/04	JC	9/20/04



FEATURES

- Diode Test
- Continuity buzzer
- Data Hold
- Display Backlight
- Full Icon Display
- Sleep Mode
- Low Battery Display
- DC Input Impedance Approx 10MΩ
- Max Display 1999
- Power: 9V Battery 6F22 (Included)
- LCD Size: 59mm x 25mm
- Weight: Approx. 275g
- Size: 165mm x 80mm x 38.3mm
- CE Compliant
- Includes Test Leads, Manual, Test Clip

Function	Range	Accuracy
DC Voltage	200mV, 2V, 20V, 200V, 1000V	±(0.5%+1)
AC Voltage	200mV, 2V, 20V, 200V, 750V	±(0.8%+3)
DC Current	20μA, 2mA, 200mA, 20A	±(0.8%+1)
AC Current	200μA, 2mA, 20mA, 200mA, 20A	±(1%+3)
Resistance	200Ω, 2kΩ, 20kΩ, 200kΩ, 2MΩ, 20MΩ, 200MΩ	±(0.8%+1)
Capacitance	2nF, 20nF, 2μF, 100μF,	±(4%+3)

SPC-F004.DWG

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	DRAWN BY:	DATE:	DRAWING TITLE:			
	Jeff McVicker	9/20/04	Advanced Autoranging Digital Multimeter			
	CHECKED BY:	DATE:	SIZE	DWG. NO.	ELECTRONIC FILE	REV
	Steve Feiwell	9/20/04	A	72-7720	02J5538.dwg	A
APPROVED BY:	DATE:	SCALE:	U.O.M.: INCHES [mm]	SHEET: 1 OF 1		
John Cole	9/20/04	NTS				

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.