

| REVISIONS |     |             | DOC. NO. SPC-F004 * Effective: 7/8/02 * DCP No: 1398 |         |        |         |        |         |
|-----------|-----|-------------|--|---------|--------|---------|--------|---------|
| DCP #     | REV | DESCRIPTION | DRAWN  | DATE    | CHECKD | DATE    | APPRVD | DATE    |
| 1740      | Α   | RELEASED    | JWM  | 9/16/04 | SF     | 9/16/04 | JC     | 9/16/04 |
|           |     |             |  | ·       |        | ·       |        | ·       |



## **FEATURES**

- 3 ¾ Digit LCD, 3999 Count, 63mm x 31mm
- Auto/ manual ranging selector
- Overmoulded cases
- · Diode, Continuity and Data hold
- Display Backlight
- Capacitance measurement
- Temperature measurement
- Frequency measurement
- Min/Max, Relative mode
- 1-Year Warranty
- Meets IEC 1010, 1000V CAT II, 600V CAT III
- CE Compliant
- Fused 10A range
- Relative Mode
- Full Icon Display
- Low Battery Display
- Sleep Mode
- Input Impedance for DCV: Approx 10MΩ
- Power: 9V Battery (6F22) Included
- Size: 177mm x 85mm x 40mm
- Weight 340g
- Includes: Test Leads, Manual, Test Clip,
  Point Contact Temperature Probe

| Function        | Range  | Accuracy  |
|-----------------|--|-----------|
| DC Voltage      | 400mV, 4V, 40V, 400V, 1000V  | ±(0.8%+1) |
| AC Voltage      | 4V, 40V, 400V, 750V  | ±(1%+5)   |
| DC Current      | 400 μ A, 4000 μ A, 40mA, 400mA, 4A, 10A  | ±(1%+2)   |
| AC Current      | 400 μ A, 4000 μ A, 40mA, 400mA, 4A, 10A  | ±(1.5%+5) |
| Resistance      | 400 $\Omega$ , 4k $\Omega$ , 40k $\Omega$ , 400k $\Omega$ , 4Μ $\Omega$ , 40Μ $\Omega$ | ±(1%+2)   |
| Capacitance     | 40nF, 400nF, 4μF, 40μF, 100μF  | ±(3%+5)   |
| Frequency       | 10Hz ~ 10MHz   | ±(0.1%+3) |
| Duty Cycle      | 0.1% ~ 99.9%   | NA        |
| Termperature °C | -40°C ~ 1000°C   | ±(1%+3)   |

SPC-F004.DWG

| TOLERANCES:                     | DRAWN BY:     | DATE:   | DRAW  | ING TITLE: |                     |             |             |     |
|---------------------------------|---------------|---------|-------|------------|---------------------|-------------|-------------|-----|
| UNLESS OTHERWISE                | Jeff McVicker | 9/16/04 |       | Advanced . | Autoranging Digi    | ital N      | Multimeter  |     |
| SPECIFIED,                      | CHECKED BY:   | DATE:   | SIZE  | DWG. NO.   |                     | ELEC        | TRONIC FILE | REV |
| DIMENSIONS ARE<br>FOR REFERENCE | Steve Feiwell | 9/16/04 | A     | 72-7740    |                     | 02J5541.dwg |             | A   |
| PURPOSES ONLY.                  | APPROVED BY:  | DATE:   |       |            |                     |             | _           |     |
|                                 | John Cole     | 9/15/04 | SCALI | E: NTS     | U.O.M.: INCHES [mm] |             | SHEET: 1 OF | - 1 |

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.