



REVISIONS

DOC. NO. SPC-F004 * Effective: 7/8/02 * DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1740	A	Released	JWM	9/14/04	SF	9/15/04	JC	9/16/04



FEATURES:

- 3 ¾ Digit LCD
- 3999 Count
- Diode and Continuity Tester
- hFE Transistor tester
- 1-Year Warranty
- Meets IEC 1010, 600V CAT I, 300V CAT II
- CE Compliant
- Power: 1.5V Battery (AAA x 2) Included
- LCD Size: 48mm x 16mm
- Weight: Approx. 156g
- Includes Test Leads, Manual, and Holster
- Low Battery Indicator

Function	Range	Accuracy
DC Voltage	400mV, 4V, 40V, 400V, 500V	±(0.8%+1)
AC Voltage	4V, 40V, 400V, 500V	±(1.2%+3)
DC Current	400µA, 4000µA, 40mA, 400mA, 4A, 10A	±(1%+2)
AC Current	400µA, 4000µA, 40mA, 400mA, 4A, 10A	±(1.5%+5)
Resistance	400Ω, 4kΩ, 40kΩ, 400kΩ, 4MΩ, 40MΩ	±(1%+2)

SPC-F004.DWG

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	DRAWN BY: Jeff McVicker	DATE: 9/14/04	DRAWING TITLE: Palm Size Digital Multimeter			
	CHECKED BY: Steve Feiwell	DATE: 9/15/04	SIZE A	DWG. NO. 72-7765	ELECTRONIC FILE 02J5546.dwg	REV A
	APPROVED BY: John Cole	DATE: 9/16/04	SCALE: NTS		U.O.M.: INCHES [mm]	SHEET: 1 OF 1

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.