

# DET4TC2 & DET4TCR2

## Digital Ground Testers



- **IP54 rated**
- **2, 3 and 4 point testing**
- **Attached Rod Technique (ART)**
- **Stakeless measurements**
- **User selectable test frequency**
- **Dry cell or rechargeable versions**
- **User selectable output voltage**
- **Simple one button operation**
- **Robust carry case**
- **Backlit display**
- **Delivered with calibration certificate**

### DESCRIPTION

Megger's DET4 family of ground testing instruments offers a comprehensive solution to your ground stake and soil resistivity testing needs. The basic kit option comprises, the instrument, test leads, stakes, batteries and calibration certificate are delivered in a tough carry case which has space to accommodate all the instrument accessories - everything you need to start testing in one kit.

The DET4TC2 and DET4TCR2 are designed for extended temperature range use with an IP54 rated enclosure making them genuinely outdoor instruments. The instrument provides all the functions required for ground system testing: variable frequency 2 pole, 3 pole, 4 pole, Attached Rod Technique (ART), stakeless, leakage current and ground noise voltage measurement.

The instrument is easy to use with a large rotary selector switch and one-press test button, both of which permit operation with gloved hands. Unlike some instruments, the design negates the need for a shorting link when making two pole measurements. There are no hidden functions with the instrument: clearly labelled auxiliary controls are used to select the test frequency (94 Hz, 105 Hz, 111 Hz and 128 Hz), output voltage (50 V or 25 V where local standards apply) and to switch the backlight on or off.

The optional ICLAMP augments the traditional fall-of-potential measurement method with ART (Attached Rod Technique) which allows electrode testing without disconnection and also leakage current measurements down to 1 mA. A second optional clamp, the VCLAMP, enables

true stakeless measurements to be made in situations where driving stakes is not practical.

The clear, easy-to-read display provides excellent contrast and viewing angle making the instrument ideally suited to outdoor use. The display is backlit, extending the operational environment of the instrument to cable cellars and other dark locations.

The instrument offers a wide measurement range of 0.01  $\Omega$  to 200 k $\Omega$ , ground noise voltage measurement from 1 V to 100 V and ground current from 1 mA to 20 A. Accurate results can be obtained in electrically noisy environments since the instrument is capable of rejecting noise voltages of 40 V peak to peak and the user can select different test frequencies to minimise the effect of interference.

The DET4TC2 Digital Ground tester is powered from 8 AA batteries which are widely available and deliver excellent testing time. The DET4TCR2 is powered from rechargeable AA cells. The battery charger is built in and the instrument is supplied with an AC/DC adaptor. For both instruments, the battery status is display using a bar-graph.

The Megger ground testers comply with stringent safety standards and are rated to 100 V CAT IV. They also have selectable 25 V or 50 V output for compliance with IEC 61557-5.

**SPECIFICATIONS**

**Ingress protection**

IP54

**C stake, P stake and Noise check**

Automatic

**Noise rejection**

40 V pk to pk

**2-wire, 3-wire, 4-wire test**

Yes, no shorting links required

**No disconnect testing (ART)**

Yes, with ICLAMP

**Stakeless measurement**

Yes, with ICLAMP and VCLAMP

**Instrument output**

Voltage:  $\pm 25$  V or  $\pm 50$  V at 94 Hz, 105 Hz, 111 Hz and 128 Hz

Current: 4.5 mA or 0.45 mA or 0.045 mA

**Ground current range with clamp**

0.5 mA to 19.9 A

**Ground current accuracy**

5%  $\pm 3$  digits

**Ground voltage range**

0 to 100 V ac

**Ground voltage accuracy**

2%  $\pm 2$  V

**Resistance range**

0.01  $\Omega$  to 200 k $\Omega$

**Resistance accuracy**

2P measurements: 2%  $\pm 3$  digits

3P measurements: 2%  $\pm 3$  digits

4P measurements: 2%  $\pm 3$  digits

ART measurements: 5%  $\pm 3$  digits

Stakeless measurements: 7%  $\pm 3$  digits

**Maximum probe resistance**

R<sub>p</sub> limit: 200 k $\Omega$  (50 V output voltage)

R<sub>c</sub> limit: 200 k $\Omega$  (50 V output voltage)

Limits reduced to 100 k $\Omega$  for 25 V output voltage

Limits reduced to 5 k $\Omega$  for 0.01  $\Omega$  resolution

**Display**

3½ digit high contrast liquid crystal, backlit

**Battery type**

**DET4TC2:** 8 off AA (LR6) cells

**DET4TCR2:** 8 off AA (LR6) NiMH rechargeable cells

**Operating temperature range**

-15°C to +55°C / 5°F to 131°F

**Storage temperature range**

-40°C to +70°C / -40°F to 158°F

**Safety**

Complies with the requirements of IEC61010-1 100V CAT IV between terminal pairs.

**EMC**

In accordance with IEC61326-1

**Standards Compliance**

Complies with the requirements of KEMA K85B

Complies with the following parts of EN61557, “Electrical safety in low voltage distribution systems up to 1000 V a.c. and 1500 V d.c. - Equipment for testing, measuring or monitoring of protective measures”.

Part 1 - General requirements

Part 5 - Resistance to earth

**Dimensions**

203 mm x 148 mm x 78 mm (8in x 5.8in x 3in)

**Weight**

1kg (2.2lb)

**ORDERING INFORMATION**

<b>Item</b>	<b>Order Code.</b>	<b>Item</b>	<b>Order Code.</b>
DET4TC2 Basic kit	1000-345	<b>Accessories</b>	
DET4TCR2 Basic kit (rechargeable)	1000-346	Replacement hard carry case	5410-429
<b>"Basic kit" included Accessories</b>		Replacement calibration check PCB (two-clamp measurements)	6220-831
Hard carry case		Replacement ground test stakes (x2) for included kit (200mm, 8mm dia)	6220-804
Stake and wire kit (15m, 10m, 10m, 3m)		Replacement ground test leads (x4) for included kit (15m, 10m, 10m, 3m)	6220-806
External AC/DC charger (DET4TCR2 only)		Replacement auger stake for professional kit	6220-839
DET4TC2 + adaptors	1000-402	Replacement cable reel (50m, red cable) for professional kit	1000-349
DET4TCR2 + adaptors (rechargeable)	1000-403	Replacement cable reel (50m, black cable) for professional kit	1000-350
<b>" + adaptors " included Accessories</b>		Replacement cable reel (30m, green cable) for professional kit	1000-362
Hard carry case		Replacement cable reel (30m, yellow cable) for professional kit	1000-361
Right angle terminal adaptors (to connect bare wires to terminals)		Replacement external AC/DC adaptor (DET4TCR2 only)	6280-370
External AC/DC charger (DET4TCR2 only)		Current clamp and connecting lead	ICLAMP
<b>Kitted options for ART and Stakeless testing</b>		Calibration check box (25 Ohm)	6220-824
DET4TC2 + clamps	1000-365	Right angle terminal adaptor set	6220-803
DET4TCR2 + clamps (rechargeable)	1000-366	Black crocodile clip (1)	6220-850
<b>" + clamps " included Accessories</b>		Professional ground testing kit (2 x 50m, 2 x 30, 4 auger stakes, tape measure, in hard carry case)	6320-245
Hard carry case		Vehicle 12 V socket charger (DET4TCR2 only)	6220-375
Stake and wire kit (15m, 10m, 10m, 3m)		"Getting down to earth"	
ICLAMP (for ART testing)		Megger guide to earth ground testing	21500-072
VCLAMP (adds stakeless testing)			
Field calibration check for instrument and CLAMPS			
Right angle terminal adaptors (to connect bare wires to terminals)			
External AC/DC charger (DET4TCR2 only)			
<b>Professional kitted options for ART and Stakeless testing</b>			
DET4TC2 + kit	1000-404		
DET4TCR2 + kit (rechargeable)	1000-405		
<b>" + kit " included Accessories</b>			
Hard carry case			
Stake and wire kit (15m, 10m, 10m, 3m)			
ICLAMP (for ART testing)			
VCLAMP (adds stakeless testing)			
Field calibration check for instrument and CLAMPS			
Right angle terminal adaptors (to connect bare wires to terminals)			
External AC/DC charger (DET4TCR2 only)			
Separate professional ground testing kit (2 x 50m, 2 x 30m, 4 auger stakes, tape measure, in hard carry case)			

**UK**

Archcliffe Road Dover  
CT17 9EN England  
T +44 (0) 1304 502101  
F +44 (0) 1304 207342  
E UKsales@megger.com

**UNITED STATES**

4271 Bronze Way  
Dallas TX 75237-1088 USA  
T 800 723 2861 (USA only)  
T +1 214 333 3201  
F +1 214 331 7399  
E USsales@megger.com

**OTHER TECHNICAL SALES OFFICES**

Norristown USA, Sydney AUSTRALIA,  
Toronto CANADA, Trappes FRANCE,  
Kingdom of BAHRAIN, Mumbai INDIA,  
Johannesburg SOUTH AFRICA, Conjure  
THAILAND and Täby SWEDEN

Registered to ISO 9001:2000 Cert. no. Q 09290  
Registered to ISO 14001-1996 Cert. no. EMS 61597  
**DET4TC2\_4TCR2\_DS\_en\_V04**

**www.megger.com**  
Megger is a registered trademark