


ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS			DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398					
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1939	Α	RELEASED	DCM	6/2/06	JWM	9/5/06	но	9/5/06



Set of 8 Mini Clips: 2 Black, 2 Red, 1 Yellow, 1 Green, 1 Blue, 1 White



Œ

SPECIFICATIONS:

- Contacts: BeCu, Gold Plated
- Snap-Locking Caps for Safety
- IEC Rating: 33 VAC / 70 VDC
- Voltage: 150 V (non-handheld)
- Current: 6 A
- Jacket Material: PVC
- Conductor Area: 0.40mm²
- Wire Gauge, Approx.: 21 AWG
- Stranding, (# x mm): 104 x 0.07mm
- Wire OD: 0.079 [2.0]
- Working temperature: -20° to +80°C

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED
HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE
BELIEVE TO BE ACCURATE AND RELIABLE. SINCE
CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE
USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT
FOR THE INTENDED USE AND ASSUME ALL RISK AND
LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

 DRAWN BY:
 DATE:

 Dan McVicker
 6/2/06

 CHECKED BY:
 DATE:

 Jeff McVicker
 9/5/06

 APPROVED BY:
 DATE:

 Hisham Odish
 9/5/06