ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. PCP * æ REVISIONS DESCRIPTION NOT released DRAWN DOC. NO. SPC-F0D5 + Effective: 12/21/98 + DCP No: 880 DATE CHECKD DATE APPRVD DATE

3421650



Excellent kit for bench meter - Straight sheath plug fits most popular bench DMM's. Leads are highly flexible silicone jacketed with safety sheath plugs. Rated to EN61010-2-031 specifications.

Probes, leads & aligator clips - 1,000V CATIII P2, 12A
Probe sprung hooks - 500V CATI P2, 3A
Spade lugs - 42V - 1,000V w/Safe User

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.								ALL ENTERDITE AND TECHNOL. NOTHATION CONTAINED HITESN ARE BREET UPON INTERNATION AND THE TREAT HE BLACKETT BE ACCURATE AND RELIGIOUS OF THE FORCE CONCIDENCE TO THE FORCE THE FORCE THE FORCE THE FORCE THE CONNECTION THEOREM.
	APPROVED BY:			CHECKED BY:		Jeff McVicker	DRAWN BY:	PURANTAM COMMIND NICED ARE BIGED UPON INFORMATIO ACCUMENT AND RELIABLE BINCE CONDITIONS OF HER ARE SYLL DITTEMAN FOR EXPOSED FOR THE BIX AND LIBITITY WATROLOGY IN COUNTRY PRETENTIN.
	DATE:			DATE:		1/29/99	DATE:	FON INFORMATION B OF USE AND RESILET FOR THE N THERENTH.
SCALE: NTS		A 76-103		SIZE DWG. NO.		General Purpose	DRAWING TITLE:	
U.O.M.: INCHES [mm]				EL		rpose DMM Kit, Straight Plugs		
SHEET: 1 OF 1		84N2145.dwg		ELECTRONIC FILE		aight Plugs		8
-				Ą				

SPC-FDG5.DWG