

datasheet for PMS 2 LMLH
 article number: 975604001



product description:	order number: 972 604-001
description:	Laboratory test lead holder with 30 plastic brackets, fastening kit and 10 measuring leads for tower construction, 2 mm safety system, Contents: 1 x Laboratory test lead holder for up to 100 measuring leads, 2 x measuring lead MVL S WS 100/1 black, 2 x measuring lead MVL S WS 100/1 red, 2 x measuring lead MVL S WS 100/1 blue, 2 x measuring lead MVL S WS 100/1 yellow, 2 x measuring lead MVL S WS 100/1 green
typ:	PMS 2 LMLH
system:	2 mm safety system
order number:	972 604-001
technical data	
measurement category	CATIII
norm	IEC 61010
pin dimensions	2 mm with laminated spring
type of contact:	spring loaded pin
type of termination:	2 mm diameter pin and socket
cable type:	LEH-XY
cable specification:	highly flexible lead
wire stranding:	259 x 0,07
rated voltage:	AC/DC 1000 V
rated current:	16 A
contact resistance:	20 mOhm
cable length:	100 cm
conductor size:	1 mm ²
cable material:	PVC
material	
contact material:	contact pin: brass, contact spring: copper berylli
contact surface material:	gold-plated
housing material:	PVC
environmental conditions:	
temperature range:	-15 °C to +70 °C
flammable class:	
housing:	UL 94 V-2
cable:	UL 94 HB