

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS				DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398						
DCP #	# REV DESCRIPTION		DRAWN	DATE	CHECKD DATE		APPRVD	DATE		
1453	Α	RELEASED	JWM	1/9/04	но	1/13/04	JC	1/23/04		



NOTES:

- Immersion probe for temperature measurements in liquids and gels
- 3 foot PVC insulated cable
- Temperature range -50°C to 1000°C [-58°F ~ 1832°F]
- Can be used with all standard K-Type thermometers and multimeters with temperature function

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED
HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE
BELIEVE TO BE ACCURATE AND RELIABLE. SINCE
CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE
USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT
FOR THE INTENDED USE AND ASSUME ALL RISK AND
LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:					
UNLESS OTHERWISE					
SPECIFIED,					
DIMENSIONS ARE					
FOR REFERENCE					
PURPOSES ONLY.					

DRAWN BY:	DATE:
Jeff McVicker	1/9/04
CHECKED BY:	DATE:
Hisham Odish	1/13/04
APPROVED BY:	DATE:
John Cole	1/23/04

	DRAWING TITLE:			_						
			K-	lype	Immersion	Prob	е			
	SIZE	DWG. NO.				ELEC.	TRONIC FIL	E		REV
4	Α	72-2062				50N1356.dwg				Α
4	SCALE: NTS			U.O.M.: INCHES [mm]			SHEET:	1	OF	1