



REVISIONS

DOC. NO. SPC-F004 \* Effective: 7/8/02 \* DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1318	A	Released	JWM	12/4/03	HO	1/19/04	JC	1/19/04



**Specifications**

- Voltage Range: 0 to +40KV DC
- Input Impedance: 600 Megohms nominal
- Accuracy: ±3% of full scale
- Calibration: Internal, factory calibrated at 25 KV
- Size: 16½" x 2⅛" x 2" with 34" cord  
[41.9cm x 5.4cm x 5cm with 86.4cm cord]
- Probe Tips: Two Interchangeable tips; one round needle type and one special flat spring type for easy access to CRT anode



**WARNING!**

**For use on Positive polarity DC voltages only!**  
*You must have a thorough understanding of the hazards that may occur when working with high voltages when using this probe. Failure to follow good safety practices could cause you serious personal harm, even death. Remember, high voltage kills if safety precautions are not followed! Be sure to read and understand the instruction manual before using this probe.*

SPC-F004.DWG

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	DRAWN BY:	DATE:	DRAWING TITLE:			
	Jeff McVicker	12/4/03	High Voltage DC Probe with Meter			
	CHECKED BY:	DATE:	SIZE	DWG. NO.	ELECTRONIC FILE	REV
	Hisham Odish	1/19/04	A	72-6530	84N1416.dwg	A
APPROVED BY:	DATE:	SCALE:	U.O.M.: INCHES [mm]	SHEET: 1 OF 1		
John Cole	1/19/04	NTS				

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.