


ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

REVISIONS		DOC. NO.	SPC-F005	* Effective:	12/21/98	* DCP No:	680	
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
615	A	RELEASED	JMM	3/2/00	JC	3/8/00	DJC	4/5/00



NOTES:

1. Rating: 1,200V, 12 Amps AC/DC
2. Materials:
Body-Polyamide (Nylon)
Plug - Bronze & Brass Nickel Plated
3. Lead Wire:
Jacket - Flexible PVC
Color: Red
Conductor: 75mm²
4. Temperature: -20°C - +80°C
5. Internal Resistance: 15 milliohms

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL. THE USER SHALL DETERMINE THE FITNESS OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
Jeff McVicker	3/2/00
CHECKED BY:	DATE:
JOHN COLE	3/8/00
APPROVED BY:	DATE:
Daniel Carey	4/5/00



DRAWING TITLE:
Plug Leads, 4mm Straight to Straight Plug

SIZE	DWG. NO.	ELECTRONIC FILE	REV
A	76-097	84N2139.dwg	A
SCALE:	NTS	U.O.M.: INCHES [mm]	SHEET: 1 OF 1