




ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART, CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS

DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1355	A	RELEASED	JWM	10/30/03	HO	11/25/03	JC	11/26/03



NOTES:

- IEC61010 Ratings: 1000V CAT III
12 Amps
Reinforced or double insulation
- Internal Resistance: 20 milliohms
- Materials: Body-Polyamide (Nylon); Plug-Bronze and Brass, Nickel plated
- Lead Wire Jacket: Extra Flexible Silicone
- Conductor: (0.75MM²)
- Temperature: -20°C to 80°C
- Color: Red



DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
Jeff McVicker	10/30/03
CHECKED BY:	DATE:
Hisham Odish	11/25/03
APPROVED BY:	DATE:
John Cole	11/26/03

DRAWING TITLE:

Sheathed Test Leads, 4mm Stacking Plugs

SIZE	DWG. NO.	ELECTRONIC FILE	REV
A	76-026	16F7697.dwg	A
SCALE: NTS	U.O.M.: INCHES [mm]	SHEET: 1 OF 1	