




ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART, CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS

DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398

| DCP # | REV | DESCRIPTION | DRAWN | DATE | CHECKD | DATE | APPRVD | DATE |
|-------|-----|-------------|-------|---------|--------|----------|--------|---------|
| 1355 | A | RELEASED | JWM | 12/1/03 | HO | 12/19/03 | JC | 1/16/04 |



NOTES:

- IEC61010 Ratings: 1000V CAT III
12 Amps
Reinforced or double insulation
- Internal Resistance: 20 milliohms
- Materials: Body-Polyamide (Nylon); Plug-Bronze and Brass, Nickel plated
- Lead Wire Jacket: Extra Flexible Silicone
- Conductor: (0.75MM²)
- Temperature: -20°C to 80°C
- Color: Black



DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

| | |
|---------------|----------|
| DRAWN BY: | DATE: |
| Jeff McVicker | 12/1/03 |
| CHECKED BY: | DATE: |
| Hisham Odish | 12/19/03 |
| APPROVED BY: | DATE: |
| John Cole | 1/16/04 |

DRAWING TITLE:

Sheathed Test Leads, 4mm Stacking Plugs

| | | | |
|--------|---------------------|-----------------|-----|
| SIZE | DWG. NO. | ELECTRONIC FILE | REV |
| A | 76-027 | 16F7698.dwg | A |
| SCALE: | U.O.M.: INCHES [mm] | SHEET: 1 OF 1 | |
| NTS | | | |