

datasheet for MLN 200/2,5 Au
article number: 934066700



| | |
|----------------------------------|---|
| product description: | order number: 934 066-700 |
| description: | Measuring lead, at either end 4 mm diameter plug with caged spring and 4 mm diameter socket for tower construction. Nickel-plated copper beryllium contact spring. Highly flexible, double insulated stranded lead, grip and lead shatter-proof. Built in colour indicator for easy identification of insulation damages. |
| typ: | MLN 200/2,5 schwarz/black Au |
| system: | 4 mm system |
| order number: | 934 066-700 |
| color | |
| other color versions: | |
| technical data | |
| pin dimensions | 4 mm |
| type of contact: | pin (spring-loaded) |
| type of termination: | 4 mm diameter pin and socket |
| cable type: | LEH-XY |
| cable specification: | highly flexible lead |
| wire stranding: | 320 x 0.10 |
| rated voltage: | DC 60 V |
| rated current: | 32 A |
| contact resistance: | 18 mOhm |
| cable length: | 200 cm |
| conductor size: | 2,5 mm ² |
| cable material: | PVC |
| cable color: | black |
| material | |
| contact material: | contact pin: brass, contact spring: copper berylli |
| contact surface material: | gold- plated |
| housing material: | PA |
| environmental conditions: | |
| temperature range: | -15 °C to +70 °C |
| inflammable class: | |
| housing: | 94 V-2 |
| cable: | 94 HB |
| drawing | |

