



testo 417

Large-Area Vane Anemometer

Direct display of volume flow, air velocity and temperature

NEW!



°C

m/s

m³/h

testo 417

Large-Area Vane Anemometer

The compact testo 417 anemometer features a fixed flow-temperature vane to measure flow, volume flow and temperature.

Volume flow is shown directly on the clear backlit display. Just input the duct measurements, and accurate volume flow calculations are automatically displayed. You can also switch between flow and temperature.

Flow direction, either from pressure or vacuum source, is visible in the display. Timed and multi-point mean calculations provide information on mean volume flow, velocity, and temperature. Min/Max values can also be displayed. The "Hold" function freezes current readings in the display making data recording easy.

- Direction recognition of flow
- Temperature, flow and volume flow measurement
- Multi-point and timed mean calculation
- Max/min values
- Hold button to freeze readings
- Display light
- Auto Off function



Using the testo 417 to monitor the air input at a ventilation outlet



Using the testo 417 to monitor the exhaust air at a wall-mounted ventilator

testo 417 anemometer with built-in 100 mm vane, including temperature measurement, battery and calibration protocol

Part no.
0560 4170

Technical data

Probe type	NTC	Vane	Volume flow
Meas. range	0 to +50 °C	+0.3 to +20 m/s	0 to +99999 m³/h
Accuracy ±1 digit	±0.5 °C	±(0.1 m/s +1.5% of mv)	
Resolution	0.1 °C	0.01 m/s	0.1 m³/h (0 to +99.9 m³/h) 1 m³/h (+100 to +99999 m³/h)
Oper. temp.	0 to +50 °C	Dimensions	277 x 105 x 45 mm
Storage temp.	-40 to +85 °C	Weight	230 g
Battery type	9V Alkali manganese	Material/Housing	ABS
Battery life	50 h	Warranty	2 years

Accessories

Accessories	Part no.
Case for measuring instrument and probes	0516 0210
Funnel set consisting of 2 attachable funnels (200 x 200 mm and 330 x 300 mm)	0563 4170
Recharger for 9V rechargeable battery For external recharging of 0515 0025 battery	900 000 0123
9V rechargeable battery for instrument Instead of battery	0515 0025
ISO velocity calibration; 5 calibration points across range 300 520 0012	300 520 0012
DKD calibration certificate/Velocity Hot wire, vane anemometer; calibration points 0.5; 1; 2; 5; 10 m/s	0520 0244

testo Ltd

Newman Lane, Alton
Hampshire, GU34 2QJ

Tel: 01420 544 433

Fax: 01420 544 434

Email: info@testo.co.uk

Web: www.testo.co.uk