



NOTES:

1. MECHANICAL CHARACTER:
 - 1.1 INSERTION FORCE: 5~25N(0.51~2.55KGf)
 - 1.2 WITHDRAW FORCE: 5~25N(0.51~2.55KGf)
 - 1.3 DURABILITY: 10000 CYCLES;
 - 1.4 INSERTION WITHDRAW FORCE 3~25N(0.3~2.55KGf) AFTER DURABILITY
2. ELECTRICAL CHARACTER:
 - 2.1. RATED VOLTAGE: 40V AC MAX.
 - 2.2. RATED CURRENT: 1 AMPERE MIN.
 - 2.3. ILCR: 10mΩ MAX.
 - 2.4. INSULATION RESISTANCE: 100MΩ MIN.
 - 2.5. DIELECTRIC WITHSTANDING VOLTAGE: 250VAC.
3. OPERATING TEMPERATURE: -40°C TD +85°C.
4. STORAGE TEMPERATURE: -40°C TD +85°C.

GENERAL TOLERANCES (UNLESS SPECIFIED)		TITLE	
4 PLACES	± 0.15	± 0.15	± 0.15
3 PLACES	± 0.30	± 0.30	± 0.30
1 PLACE	± 0.30	± 0.30	± 0.30
ANGULAR DIM.		ANGULAR DIM.	

REV. NO.	CHANGE DESCRIPTION	DATE	BY
X2	RELEASED	2010/01/19	Ning Wang
	CHANGE DESCRIPTION	2010/01/19	Ning Wang

REV. NO.	CHANGE DESCRIPTION	DATE	BY
X2	RELEASED	2010/01/19	Ning Wang
	CHANGE DESCRIPTION	2010/01/19	Ning Wang

ALL RIGHTS RESERVED TO APHENOL
 THIRD ANGLE PROJECTION
 Amphenol Tianjin