



Home > Products > Discrete Thermistors > 135 > Product Page

### Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- RoHS Product List
- Customer Feedback

## 135-105QAF-J01



Actual product appearance may vary.

### Glass encapsulated chip DO -35 type

#### Features

Cost effective  
Rugged DG35 glass encapsulation  
High temperature capability  
Available on tape and reel

#### Potential Applications

Consumer electronics  
PCB temperature sensing  
Communications  
Fire detection  
Computers  
Low -cost applications with a maximum temperature of 300 °C [615 °F]  
Automotive

#### Description

135 Series Thermistors are high-quality, hermetically-sealed, glass-encapsulated units in an axial lead package. They cover the full temperature range of -60 °C to 300 °C [-76 °F to 572 °F]. The uniform dimensions are often suited for automated assembly. The tinned copperclad, steel leads are both solderable and weldable. These rugged sensors are designed for many applications which demand reliability at low cost. Available on tape and reel for automated assembly.

#### Supporting Documentation

None Available

Product Specifications	
Availability	Global
Nominal Resistance at 25 °C [77 °F]	1,000,000 Ohm
Tolerance	± 5.0%
Accuracy	25 °C [77 °F]
R- T Curve	1
Operating Temperature Range	- 60 °C to 300 °C [ - 76 °F to 572 °F]
Maximum Diameter	2,0 mm [0.080 in]
Termination Material	Tinned copper - clad steel
Lead length	28,6 mm [1.125 in]
Time Constant in Air	4.0 s
Dissipation Constant	2,5 m/W°C
Series Name	135

#### My Links

[Login to iCOM](#)  
[Login as Rep/AD](#)  
[Login as Guest](#)  
[Login to Digital University](#)

#### Keyword Search

Search for product and support information.

All Sensing and Control

#### Product Search

Part number search:

Use (\*) to expand search

Specification Search