



(2,00mm) .0787" **TCSD SERIES**







TIGER EYE" IDC SOCKET CABLE

Mates with: TMM, TMMH, STMM, MMT, TW, MTMM, EHT, ETMM (-SR), ZSTMM

FEATURES

- Low profile, only 5mm (.200") assembled height
- Four-finger contacts optimize normal, insertion and withdrawal forces
- Ask about our custom IDC design capabilities

SPECIFICATIONS

For complete specifications

Black Glass Filled Polvester Contact:

BeCu Plating:

Au or Šn over 50μ" (1,27μm) Ni

28 AWG 7/36 Stranded, Tinned, Copper with Gray PVC Insulator Current Rating:

Operating Temp Range: -40°C to +105°C

Lead Size Accepted: (0,48mm) .019" to (0,53mm) .021" Contact Resistance: 15 mQ maximum delta from initial Insertion Depth: (2,87mm) .113" to (3,17mm) .125" Insertion Force:

(Single contact only) 2 oz. (0,56N) average Withdrawal Force: (Single contact only) 1.4 oz (0,39N) average


RoHS Compliant:


POLARIZING KEY


Specify PK-01-07 for polarizing key (Available in wheels of six each). Also polarizes SMM Series socket strips.

Note: Other Gold plating options available. Contact Samtec.


Note: TCSD Series assemblies are nonstandard, non-returnable,







Specify "XX" as number of conductors to be broken out Breakout starts with Number 1 lead indicated by brown wire or red stripe. Shown on top side. -RW = Reverse Wiring Blue or black wire opposite position #1.



Requires -DXX