


NOTE:
 1. PIN CONNECTION IS 1 TO 1 ACCORDING TO TABLE
 2. PLACE TIE WRAP IN THE MIDDLE OF THE ASSEMBLY APPROX.
 3. APPLY LABEL WITH LEGEND "1" OR "2" ACCORDING TO DRAWING

WIRING CHART

EXT. "A"	COLOR	EXT. "B"
1	WHITE	1
2	BLACK	2
3	RED	3
4	GREEN	4
5	YELLOW	5
6	BLUE	6

ROHS

ITEM	P/N	DESCRIPTION	QTY
4	0799212000	LABEL	5 PC
3	0799617946	TIE WRAP BLACK NYLON	3 PC
2	0799232239	OVAL BK CABLE 6 COND, 26AWG JACKETED	A/R
1	0900750031	PLUG 6/6 LOOSE 900750031	4 PC



RELEASED EC NO: MEX2008-0049 DRWN: AOROZCO 2007/11/13 CHKD: ACUEVAS 2007/11/13 APPR: ACUEVAS 2007/11/13	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
		4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± --- 1 PLACE ± --- ± ---	mm INCH	DRAWN BY AOROZCO	DATE 02/02/2007	TITLE WIRE, SWITCH UPPER RWD 9432			
		ANGULAR ± ---°		CHECKED BY AOROZCO	DATE 02/02/2007	MOLEX INCORPORATED			
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPROVED BY ACUEVAS	DATE 02/02/2007	MATERIAL NO. 79616-0016	DOCUMENT NO. SD-79616-0016	SHEET NO. 1 OF 1	

tb_frame_A_P_ME_T
 Rev. E 2006/04/15