
# 3M<sup>™</sup> MetPak<sup>™</sup> HSHM Press-Fit Socket

2 mm Type FL, 88 Signal Contacts, 8 Rows, Right Angle

**HM Series** 



- Modular/scalable format IEC 61076-4-101
- 101 mated lines per linear inch
- Dual beam contact construction for high reliability
- End-to-end stackable with 8 row 3M<sup>™</sup> MetPak<sup>™</sup> HM and HSHM products
- Mates with 3M<sup>™</sup> MetPak<sup>™</sup> HSHM headers
- See the Regulatory Information Appendix (RIA) in the "RoHS compliance" section of www.3mconnector.com for compliance information

Date Modified: October 11, 2010

TS-2023-B Sheet 1 of 3

800-225-5373

# **Physical**

**Insulation:** 

Material: High Temperature Thermoplastic (LCP)

Flammability: UL 94V-0

**Contact:** 

Material: Copper Alloy

Plating: See Ordering Information

Marking: 3M Logo, Part Number, Revision, Date Code

## **Performance**

### **Mechanical:**

Normal Force (Nominal): 0.57 N [58 g] Signal Engagement Force (Nominal): 0.32 N [33 g] Signal Separation Force (Nominal): 0.20 N [20 g] Signal Wipe (Nominal, Shortest Contact): 2.67 mm [0.105 in] Signal

Mate/Unmate Cycles: 250

Application: This module is not suitable for stand-alone use.

**Electrical:** 

Current Rating (Fully Loaded): 1 A @ 70°C Signal Insulation Resistance:  $1 \times 10^4 M\Omega$  @  $100 V_{DC}$ 

Withstanding Voltage: 750 V<sub>RMS</sub>

### **Environmental**

**Temperature Rating:** -55° C to 125° C

UL File No.: E68080 MetPak is a trademark of 3M Company.

**3M** 

3M is a trademark of 3M Company. For technical, sales or ordering information call


Interconnect Solutions http://www.3Mconnector.com

**Electronic Solutions Division** 

# 3M<sup>™</sup> MetPak<sup>™</sup> HSHM Press-Fit Socket

2 mm Type FL, 88 Signal Contacts, 8 Rows, Right Angle


**HM Series** 



**3M** 

Electronic Solutions Division Interconnect Solutions http://www.3Mconnector.com 3M is a trademark of 3M Company. For technical, sales or ordering information call 800-225-5373 2 mm Type FL, 88 Signal Contacts, 8 Rows, Right Angle

**HM Series** 



Recommended PCB hole mounting pattern

Hole Plating Table mm [in.]			
Finished Hole Dia. "D"	Cu. Thickness	SnPb Thickness	Drilled Hole Dia.
0.550-0.650 [.02170256]	0.025 - 0.045 [.00100018]	0.008 -0.018 [.00030007]	0.686-0.727 [.02700286]

TS-2023-B Sheet 3 of 3

#### **Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

#### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.



**3M Electronics Solutions Division** 

6801 River Place Blvd. Austin, TX 78726-9000 U.S.A. 1-800-225-5373 www.3Mconnector.com

Please recycle. Printed in USA. © 3M 2010. All rights reserved. RIA-2217B-E

3M is a trademark of 3M Company.