



RECOMMENDED PC BOARD MOUNTING DIMENSIONS
 FOR .063 [1.60] THICK PC BOARD AND
 .012 [0.305] STENCIL THICK.

- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- 0.00762 [0.00030] GOLD IN CONTACT AREA, 0.00254-0.00508 [0.000100-0.000200] MATTE TIN-LEAD ON SOLDER TAIL, ALL OVER 0.00127 [0.00050] NICKEL.
- MATERIAL: HOUSING - LCP, COLOR: BLACK, POSTS - PHOSPHOR BRONZE
- 0.00762 [0.00030] GOLD IN CONTACT AREA, 0.00254-0.00508 [0.000100-0.000200] MATTE TIN ON SOLDER TAIL, ALL OVER 0.00127 [0.00050] NICKEL.
- OBsolete PARTS: OBsolete CIS STREAMLINING PER D.RENAUD/D.SINISI

NO	DEF	T	UN	REVISIONS	DATE	BY	APP
101.19	99.06	39	40	9-146281-0			
101.19	99.06	39	40	4-146281-0			
13.984	13.900	38	39	8-146281-9			
13.984	13.900	38	39	3-146281-9			
96.11	93.98	37	38	8-146281-8			
96.11	93.98	37	38	3-146281-8			
93.57	91.44	36	37	8-146281-7			
93.57	91.44	36	37	3-146281-7			
3.684	3.600	35	36	8-146281-6			
3.684	3.600	35	36	3-146281-6			
88.49	86.36	34	35	8-146281-5			
88.49	86.36	34	35	3-146281-5			
85.95	83.82	33	34	8-146281-4			
85.95	83.82	33	34	3-146281-4			
3.284	3.200	32	33	8-146281-3			
3.284	3.200	32	33	3-146281-3			
80.87	78.74	31	32	8-146281-2			
80.87	78.74	31	32	3-146281-2			
78.33	76.20	30	31	8-146281-1			
78.33	76.20	30	31	3-146281-1			
2.984	2.900	29	30	8-146281-0			
2.984	2.900	29	30	3-146281-0			
73.79	71.66	28	29	7-146281-9			
73.79	71.66	28	29	2-146281-9			
70.71	68.58	27	28	7-146281-8			
70.71	68.58	27	28	2-146281-8			
68.17	66.04	26	27	7-146281-7			
68.17	66.04	26	27	2-146281-7			
65.63	63.50	25	26	7-146281-6			
65.63	63.50	25	26	2-146281-6			
63.09	60.96	24	25	7-146281-5			
63.09	60.96	24	25	2-146281-5			
2.484	2.400	23	24	7-146281-4			
2.484	2.400	23	24	2-146281-4			
60.55	58.42	22	23	7-146281-3			
60.55	58.42	22	23	2-146281-3			
55.47	53.34	21	22	7-146281-2			
55.47	53.34	21	22	2-146281-2			
2.184	2.100	20	21	7-146281-1			
2.184	2.100	20	21	2-146281-1			
50.39	48.26	19	20	7-146281-0			
50.39	48.26	19	20	2-146281-0			
47.85	45.72	18	19	6-146281-9			
47.85	45.72	18	19	1-146281-9			
1.884	1.800	17	18	6-146281-8			
1.884	1.800	17	18	1-146281-8			
45.11	43.18	16	17	6-146281-7			
45.11	43.18	16	17	1-146281-7			
1.684	1.600	15	16	6-146281-6			
1.684	1.600	15	16	1-146281-6			
40.23	38.10	14	15	6-146281-5			
40.23	38.10	14	15	1-146281-5			
1.484	1.400	13	14	6-146281-4			
1.484	1.400	13	14	1-146281-4			
37.69	35.56	12	13	6-146281-3			
37.69	35.56	12	13	1-146281-3			
33.07	31.14	11	12	6-146281-2			
33.07	31.14	11	12	1-146281-2			
27.53	25.40	10	11	6-146281-1			
27.53	25.40	10	11	1-146281-1			
24.99	22.86	9	10	6-146281-0			
24.99	22.86	9	10	1-146281-0			
22.45	20.32	8	9	5-146281-9			
22.45	20.32	8	9	146281-9			
19.91	17.78	7	8	5-146281-8			
19.91	17.78	7	8	146281-8			
17.37	15.24	6	7	5-146281-7			
17.37	15.24	6	7	146281-7			
14.83	12.70	5	6	5-146281-6			
14.83	12.70	5	6	146281-6			
12.29	10.16	4	5	5-146281-5			
12.29	10.16	4	5	146281-5			
9.75	7.62	3	4	5-146281-4			
9.75	7.62	3	4	146281-4			
7.21	5.08	2	3	5-146281-3			
7.21	5.08	2	3	146281-3			
4.67	2.54	1	2	5-146281-2			
4.67	2.54	1	2	146281-2			
2.13	-	0	1	5-146281-1			
2.13	-	0	1	146281-1			

THIS DRAWING IS A CONTROLLED DOCUMENT. IT IS THE PROPERTY OF TE CONNECTIVITY. IT IS TO BE USED ONLY FOR THE PURPOSES AND IN THE QUANTITIES SPECIFIED IN THE ORDER. IT IS NOT TO BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE EXPRESS WRITTEN PERMISSION OF TE CONNECTIVITY.

TE Connectivity
 TE CONNECTIVITY
 TE CONNECTIVITY
 TE CONNECTIVITY

HEADLINE ASSEMBLY, MOD II, BREAKAWAY, SINGLE ROW, HIGH TEMPERATURE, VERTICAL W/O/SO POSTS, 100 E

DATE: 00779G-146281

CUSTOMER DRAWING