


Thick Film Planar Resistors and Dividers, Through-Hole, High Voltage



APPLICATIONS

Applications include power supplies, transformers and any application requiring operation within an environment where high voltages are used.

FEATURES

- 30 000 V capability
- Very low voltage coefficient to less than 1 ppm/V
- Outstanding stability under adverse conditions
- Stable cermet resistive element bonded to a high-purity alumina substrate
- Tough epoxy-based coating and high voltage stability
- Designs built from customer supplied schematics
- Dividers available leaded or non-leaded
- Typical resistance ratios of 1000:1, 2000:1, etc.
- TCR tracking to ± 5 ppm/ $^{\circ}$ C depending on values
- TD series dividers available, contact factory
- Compliant to RoHS directive 2002/95/EC
- Halogen-free according to IEC 61249-2-21 definition



RoHS
COMPLIANT
HALOGEN
FREE

STANDARD ELECTRICAL SPECIFICATIONS					
GLOBAL MODEL/ SIZE	POWER RATING $P_{25^{\circ}\text{C}}$ W	MAXIMUM WORKING VOLTAGE V ⁽¹⁾	RESISTANCE RANGE Ω ⁽²⁾	TOLERANCE $\pm \%$	TEMPERATURE COEFFICIENT \pm ppm/ $^{\circ}$ C
TR03C	0.25	0.8K	300 to 3M	1, 2, 5, 10, 20	100
TR03X			2.5K	300 to 25M	1, 2, 5, 10, 20
		25M to 250M		1, 2, 5, 10, 20	200, 300
				260M to 2G	5, 10, 20
			2.1G to 10G	5, 10, 20	⁽³⁾
TR05D	0.5	4K	500 to 25M	1, 2, 5, 10, 20	100
TR05X			5K	3K to 200M	1, 2, 5, 10, 20
				30M to 1G	1, 2, 5, 10, 20
				1.1G to 20G	5, 10, 20
			21G to 100G	5, 10, 20	⁽³⁾
TR10F	1	6.5K	1K to 16M	1, 2, 5, 10, 20	100
TR10X			10K	2K to 120M	1, 2, 5, 10, 20
				20M to 1G	1, 2, 5, 10, 20
				1.1G to 15G	5, 10, 20
			16G to 1T	5, 10, 20	⁽³⁾
TR15G	1.5	12.5K	1.5K to 45M	1, 2, 5, 10, 20	100
TR15X			15K	5K to 340M	1, 2, 5, 10, 20
				60M to 1G	1, 2, 5, 10, 20
				1.1G to 35G	5, 10, 20
			36G to 1.5T	5, 10, 20	⁽³⁾
TR20H	2	17.5K	2K to 64M	1, 2, 5, 10, 20	100
TR20X			20K	8K to 480M	1, 2, 5, 10, 20
				80M to 1G	1, 2, 5, 10, 20
				1.1G to 50G	5, 10, 20
			51G to 2T	5, 10, 20	⁽³⁾
TR30J	3	25K	3K to 82M	1, 2, 5, 10, 20	100
TR30X			30K	8.5K to 620M	1, 2, 5, 10, 20
				80M to 1G	1, 2, 5, 10, 20
				1.1G to 60G	5, 10, 20
			61G to 3T	5, 10, 20	⁽³⁾


Notes

- Custom sizes available
 - Voltage coefficient: Typically less than 1 ppm/V (tested per MIL-STD-202)
 - Ratio tolerance for dividers: 1 % to 20 %
 - Ratio TCR for dividers: To ± 5 ppm/ $^{\circ}$ C (ratio over 1000:1, contact factory)
- ⁽¹⁾ Continuous working voltage shall be $\sqrt{P \times R}$ or maximum working voltage, whichever is less.
⁽²⁾ All resistance values are calibrated at 100 V_{DC}. Calibration at other voltages available upon request.
⁽³⁾ Contact factory


* Pb containing terminations are not RoHS compliant, exemptions may apply

GLOBAL PART NUMBER INFORMATION

New Global Part Numbering: TR20H1K00FKEB (preferred part number format)



Historical Part Numbering: TR20H1001FKe3 (will continue to be accepted)



MECHANICAL SPECIFICATIONS


Resistive Element: Thick film
Substrate: 96 % pure alumina
Encapsulation: Epoxy base, conformal coating
Terminals: Tin plated copper leads
Terminal Strength: 4.5 pounds pull-test
Power: Derated from ambient temperature + 25 °C

ENVIRONMENTAL SPECIFICATIONS


Temperature Range: - 55 °C to + 125 °C (for higher temperature range, consult factory)
Load Life: Less than 0.15 %, 1000 h

DIMENSIONS in inches (millimeters)


Typical Resistor Schematic for Divider



Typical High Voltage Divider




Standard High Voltage Resistor



DIMENSIONS (± 10 %)

MODEL	A (LENGTH)	B (HEIGHT)	C (LEAD SPACING)	D (LEAD DIA.)
TR03	0.300 (7.62)	0.210 (5.33)	0.200 (5.08)	0.025
TR05	0.500 (12.70)	0.300 (7.62)	0.400 (10.16)	0.025
TR10	1.00 (25.40)	0.350 (8.89)	0.900 (22.86)	0.032
TR15	1.50 (38.10)	0.350 (8.89)	1.40 (35.56)	0.032
TR20	2.00 (50.80)	0.350 (8.89)	1.90 (48.26)	0.032
TR30	3.00 (76.20)	0.400 (10.16)	2.90 (73.66)	0.032

DERATING





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.