

Power Resistor for Mounting onto a Heatsink Thick Film Technology



FEATURES


- High power rating
- Low thermal radiation of the case
- Wide ohmic value range
- Easy mounting
- High overload capabilities
- Reduced size and weight
- Compliant to RoHS directive 2002/95/EC



This new style has been developed as an extension to RCH range. Through the use of thick film technology, a non-inductive solution for power resistors is available which are rated up to 100 W at + 25 °C. The terminations position prevents any risk of an electrical arc to the heatsink. This resistor series can replace and offer advantages to standard wirewound devices.

DIMENSIONS in millimeters

RPH 100



Note

- Tolerance unless otherwise specified: ± 0.3 mm

MECHANICAL SPECIFICATIONS

Mechanical Protection	Insulated case
Substrate	Alumina on metallic base of nickel coated aluminum
Resistive Element	Cermet
End Connections	V connections: Screws M4 x 6
Tightening Torque Connections	1 Nm
Tightening Torque Heatsink	3 Nm
Weight	60 g

ENVIRONMENTAL SPECIFICATIONS

Thermal Resistance	$R_{TH(j-c)}$ 0.55 °C/W
Temperature Range	- 55 °C to + 125 °C
Climatic Category	55/125/56

ELECTRICAL SPECIFICATIONS

Resistance Range	0.092 Ω to 1 MΩ E24 series
Tolerances	± 1 % to ± 10 %
Power Rating:	
Continuous	100 W at 25 °C chassis mounted 0.45 °C/W 10 W at 25 °C free air
Momentary	400 W at 25 °C for 5 s
Temperature Coefficient	
Standard	± 300 ppm/°C < 1 Ω ± 150 ppm/°C > 1 Ω
Limiting Element Voltage U_L	1900 V _{RMS}
Dielectric Strength MIL STD 202	5 kV _{RMS} 1 min 10 mA max.
Insulation Resistance	> 10 ⁶ MΩ
Inductance	< 0.1 μH

PERFORMANCE		
TESTS	CONDITIONS	REQUIREMENTS
Short Time Overload	NF EN 140000 CEI 115_1 $4 P_n/5 s U_S < 2 U_L$	$< \pm (0.25 \% + 0.05 \Omega)$
Rapid Temperature Change	NF EN 140000 CEI 68214 Test Na 5 cycles - 55 °C + 125 °C	$< \pm (0.25 \% + 0.05 \Omega)$
Load Life (Chassis Mounted 0.45 °C/W)	NF EN 140000 P_n at 25 °C 1000 h	$< \pm (0.5 \% + 0.05 \Omega)$
Humidity (Steady State)	MIL STD 202 Method 103 B Test D 56 days 95 % RH	$< \pm (0.5 \% + 0.05 \Omega)$

RESISTANCE VALUE IN RELATION TO TOLERANCE AND TCR		
Ohmic Value	$< 1 \Omega$	$> 1 \Omega$
Standard Tolerance	$\pm 5 \%$	$\pm 5 \%$
Standard TCR	$\pm 300 \text{ ppm}/^\circ\text{C}$	$\pm 150 \text{ ppm}/^\circ\text{C}$
Tolerance On Request	$\pm 1 \% - \pm 2 \%$	

RECOMMENDATIONS FOR MOUNTING ONTO A HEATSINK

- Surfaces in contact must be carefully cleaned.
- The heatsink must have an acceptable flatness: From 0.05 mm to 0.1 mm/100 mm.
- Roughness of the heatsink must be around 6.3 μm . In order to improve thermal conductivity, surfaces in contact (alumina, heatsink) should be coated with a silicone grease (type SI 340 from Rhône-Poulenc or Dow 340 from Dow Corning).
- The fastening of the resistor to the heatsink is under pressure control of four screws (not supplied).

Tightening Torque on Heatsink	RPH 100
	3 Nm

- In order to improve the dissipation, either forced-air cooling or liquid cooling may be used.
- Do not forget to respect an insulation value between two resistors (dielectric strength in dry air 1 kV/mm).

CHOICE OF THE HEATSINK

The user must choose according to the working conditions of the component (power, room temperature). Maximum working temperature must not exceed 125 °C. The dissipated power is simply calculated by the following ratios:

$$P = \frac{\Delta T}{[R_{TH(j-c)} + R_{TH(c-a)}]} \quad (1)$$

P: Expressed in W

T: Difference between maximum working temperature and room temperature.

$R_{TH(j-c)}$: Thermal resistance value measured between resistive layer and outer side of the resistor.
It is the thermal resistance of the component: 0.55 °C/W.

$R_{TH(c-a)}$: Thermal resistance value measured between outer side of the resistor and room temperature.
It is the thermal resistance of the heatsink itself (type, shape) and the quality of the fastening device.

Example:

$R_{TH(c-a)}$: For RPH 100 power rating 80 W at ambient temperature + 40 °C.

Thermal resistance $R_{TH(j-c)}$: 0.55 °C/W

Considering equation (1) we have:

$$\Delta T \leq 125 \text{ °C} - 40 \text{ °C} \leq 85 \text{ °C}$$

$$R_{TH(j-c)} + R_{TH(c-a)} = \frac{\Delta T}{P} = \frac{85}{80} = 1.06 \text{ °C/W}$$

$$R_{TH(c-a)} \leq 1.06 \text{ °C/W} - 0.55 \text{ °C/W} \leq 0.51 \text{ °C/W}$$

OVERLOADS

In any case the applied voltage must be lower than $2 U_n$.
 $U_{max.} < 2 U_n < 3800 V$.



Short time overload: $4 P_n/5 s$.

Accidental overload: The values indicated on the graph below are applicable to resistors in air or mounted onto a heatsink.

POWER RATING

For resistor mounted onto a heatsink with thermal resistance of $0.45 \text{ }^\circ\text{C/W}$.

ENERGY CURVE



MARKING

Series, style, ohmic value (in Ω), tolerance (in %), manufacturing date, Vishay Sfernice trademark.

ORDERING INFORMATION					
RPH	100	3.3 k Ω	$\pm 5 \%$	V	XXX
MODEL	STYLE	RESISTANCE VALUE	TOLERANCE	CONNECTIONS	CUSTOM DESIGN
			Optional $\pm 1 \%$ $\pm 2 \%$ $\pm 5 \%$	V: M4 screw	Options on request TCR, shape, etc.

GLOBAL PART NUMBER INFORMATION														
R	P	H	1	0	0	V	1	0	0	0	2	J	B	
GLOBAL MODEL	SIZE	LEADS	OHMIC VALUE				TOLERANCE	PACKAGING	SPECIAL					
RPH	100	V = M4 screw	The first four digits are significant figures and the last digit specifies the number of zeros to follow. R designates decimal point. 48R70 = 48.7 Ω 48701 = 48 700 Ω 10002 = 100 k Ω R0100 = 0.01 Ω R6800 = 0.68 Ω 27000 = 2700 Ω = 2.7 k Ω				F = 1 % G = 2 % J = 5 % K = 10 %	B = Box 5 pieces	As applicable Ex = XXX					



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.