


REV. 0  
DCO 140801

|                 |                            |
|-----------------|----------------------------|
| COIL: @ 25°C    |                            |
| RESISTANCE      | 390 OHMS ± 10%             |
| NOMINAL VOLTAGE | 12.0 VDC                   |
| MUST OPERATE    | 7.0 VDC                    |
| MUST RELEASE    | 4.0 VDC MAX. 0.63 VDC MIN. |

|              |                             |
|--------------|-----------------------------|
| ENVIRONMENT: |                             |
| VIBRATION    | 10 CPS TO 3000 CPS @ 30 g's |
| SHOCK        | 75 g's 6 MS. DURATION       |
| TEMPERATURE  | -65 °C TO +125 °C           |

|        |                                  |
|--------|----------------------------------|
| NOTES: | OPERATE TIME 2.0 MS MAX          |
|        | RELEASE TIME 4.0 MS MAX          |
|        | CONTACT STABILIZATION 2.5 MS MAX |

CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO 1 AMP  
28 VDC RESISTIVE 100,000 OPERATIONS

DR. R.B. 12/11/98 CK: JERRA 12/11/98



CUST. QPL  
CUST. NO. M39016/18-040M

TYPE JMGAD RELAY

JMGACD-12MW