

# PME278RA4330MR30

aka P278HH332M440A

Capacitor, film, 3300 pF, +/-20% Tol, -40/+110C, Safety: X1, 440VAC,  
Lead Spacing=10.2 mm



## Dimensions (mm)

| ID | Dimension | Tolerance |
|----|-----------|-----------|
| L  | 13.5      | max       |
| H  | 8.2       | max       |
| T  | 4.1       | max       |
| S  | 10.2      | +/-0.4    |
| LL | 30        | nom       |
| F  | 0.6       | nom       |

## Specifications

|                             |                  |
|-----------------------------|------------------|
| Manufacturer:               | KEMET            |
| Brand:                      | Rifa             |
| Capacitance:                | 3300 pF          |
| Temperature Range:          | -40/+110C        |
| Rated Temperature:          | 110C             |
| Voltage @ rated temp:       | 1000V            |
| Voltage AC:                 | 440VAC           |
| Tolerance:                  | +/-20%           |
| Body Type:                  | Radial Molded    |
| Construction:               | Non-inductive    |
| Application:                | Safety: X1       |
| Dielectric:                 | Metallized Paper |
| Dissipation Factor @ 1 kHz: | 1.3%             |
| Insulation Resistance:      | 12 GOhm          |
| Maximum dVdT:               | 2000v/us         |
| IEC_60384-14:               | 440V             |
| EN_132400:                  | 440V             |
| Miscellaneous Electrical:   | PME278           |
| Package Kind:               | Bulk             |
| Package Quantity:           | 1000             |