

**Tyco Electronics**

Our commitment. Your advantage.

Search

[Products](#) ▾ [Documentation](#) ▾ [Resources](#) ▾ [My Account](#) ▾ [Customer Support](#)[Home](#) > [Products](#) > [By Type](#) > [PolySwitch Resettable Devices](#) > [Product Feature Selector](#) > Product Details**SMD100F/33-2 Product Details****SMD100F/33-2**TE Internal Number:
A45463-000✓ [Active](#)**PolySwitch Resettable Devices**✓ [Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))**Product Highlights:**

- Surface Mount Application
- Family Name = SMD
- Surface Mount Construction
- IH (Room Temperature) = 1.1 Amps.
- IT (Room Temperature) = 2.20 Amps.

[View all Features](#)**Quick Links**

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#)**Documentation & Additional Information****Product Drawings:**

- [SMD100F/33](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)**Product Features** (Please use the Product Drawing for all design activity)**Product Type Features:**

- UL Recognized = 191099-E74889
- CSA File No. = 1031175 (CA 78165-1)

Electrical Characteristics:

- [IH \(Room Temperature\) \(Amps.\)](#) = 1.1
- [IT \(Room Temperature\) \(Amps.\)](#) = 2.20
- [Vmax Operating \(V\)](#) = 33
- [Rmin \(Ω\)](#) = 0.12
- [R1 Max \[Post Trip\] \(Ω\)](#) = 0.41
- [UL Rated Current \(Amps.\)](#) = 40
- Tripped Power Dissipation (Typical) (W) = 1.70

Termination Related Features:

- Construction = Surface Mount

Contact Related Features:

- [Family Name](#) = SMD

Configuration Related Features:

- [Form Factor \(inches\)](#) = 2920
- [Form Factor \(mm\)](#) = 7555

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041427

Conditions for Usage:

- [Operating Temperature \(Max.\) \(°C\)](#) = 85

Operation/Application:

- Application = Surface Mount

Packaging Related Features:

- Packaging Method = Tape & Reel

Other:

- Brand = Raychem

[Provide Website Feedback](#) | [Need Help?](#)[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2009 Tyco Electronics Corporation All Rights Reserved