Our commitment. Your advantage.

Search

Product

Documentation

Resources

My Account

Customer Support

Home > Products > By Type > PolySwitch Resettable Devices > Product Feature Selector > Product Details

RXEF185-2 Product Details



RXEF185-2

Raychem Part Number: F01480-000

PolySwitch Resettable Devices

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Radial Application
- Family Name = RXEF
- Radial Construction, Through Hole Construction
- IH (Room Temperature) = 1.85 Amps.
- IT (Room Temperature) = 3.70 Amps.

View all Features

Quick Links

Check Pricing & Availability Search for Tooling Product Feature Selector Contact Us About This Product

Documentation & Additional Information

Product Drawings:

• RXEF185 (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

• None Available

CAD Files:

None Available

Additional Information:

• Product Line Information

Related Products:

Tooling

<u>List all Documents</u>

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

• UL Recognized = File No. E74889

Electrical Characteristics:

- IH (Room Temperature) (Amps.) = 1.85
- IT (Room Temperature) (Amps.) = 3.70
- Vmax Operating (V) = 72
- Rmin(?) = 0.08
- Rmax(?) = 0.120
- R1 Max [Post Trip] (?) = 0.19
- <u>UL Rated Current (Amps.)</u> = 40
- Tripped Power Dissipation (Typical) (W) = 2.10

Termination Related Features:

• Construction = Radial, Through Hole

Body Related Features:

- Lead Type = Straight
- CSA File No. = 78165C

Contact Related Features:

Family Name = RXEF

Configuration Related Features:

Coating = Coated

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041428

Conditions for Usage:

• Operating Temperature (Max.) (°C) = 85

Operation/Application:

Application = Radial

Packaging Related Features:

Packaging Method = Tape & Reel

Other:

• Brand = Raychem

Provide Website Feedback | Contact Customer Support