



Search by Keyword or Part #

MINISMDC150F-2 Product Details



MINISMDC150F-2

TE Internal Number: RF1408-000

[Active](#)

PolySwitch Resettable Devices

[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Surface Mount Application
- Vmax = 6 V
- Imax = 100 A
- Family Name = miniSMD
- Surface Mount Construction

[View all Features](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> ● None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> ● None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> ● miniSMD150F (PDF, English) <p>Application Specifications:</p> <ul style="list-style-type: none"> ● None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> ● None Available <p>CAD Files:</p> <ul style="list-style-type: none"> ● None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> ● Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> ● Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> ● UL File Number = E74889 ● CSA File Number = CA78165 <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> ● Vmax (V) = 6 ● Imax (A) = 100 ● IH (Room Temperature) (A) = 1.5 ● IT (Room Temperature) (A) = 3.00 ● Rmin (Ω) = 0.04 ● RI Max [Post Trip] (Ω) = 0.11 <p>Termination Related Features:</p> <ul style="list-style-type: none"> ● Construction = Surface Mount <p>Contact Related Features:</p> <ul style="list-style-type: none"> ● Family Name = miniSMD <p>Configuration Related Features:</p> <ul style="list-style-type: none"> ● Form Factor (inches) = 1812 ● Form Factor (mm) = 4532 	<p>Industry Standards:</p> <ul style="list-style-type: none"> ● RoHS/ELV Compliance = RoHS compliant, ELV compliant ● Lead Free Solder Processes = Reflow solder capable to 245°C, Reflow solder capable to 260°C ● RoHS/ELV Compliance History = Always was RoHS compliant ● TUV Certificate No. = R72041438 <p>Conditions for Usage:</p> <ul style="list-style-type: none"> ● Operating Temperature (Max.) (°C) = 85 <p>Operation/Application:</p> <ul style="list-style-type: none"> ● Application = Surface Mount <p>Packaging Related Features:</p> <ul style="list-style-type: none"> ● Packaging Method = Tape & Reel <p>Other:</p> <ul style="list-style-type: none"> ● Brand = Raychem



Corporate Information

- [Who We Are](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat with Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)

Sign up for our eNewsletter

Enter your email address

Follow Us On:

Twitter Facebook LinkedIn YouTube

Visit Us On:



[Provide Website Feedback](#)