Skip to content

<u>Corporate Home</u> | Delectronic Components | <u>Segments</u> | <u>Who We Are</u> Worldwide



Our commitment. Your advantage.

Search By:

×

•	Products
Þ	
	Connectors
	Electromechanical Components
	Electronic Modules
	Fiber Optics
	Filters
	Identification Labeling Products
	Passive Components
	Power Sources
	RF & Microwave Products
	Tooling Products
	Touch Screen Displays
	Tubing, Molded and Harnessing Products
	Wire, Cable and Cable Assemblies
	List all Product Types

http://catalog.tycoelectronics.com/TE/bin/TE.Connect?C=1&M=BYPN&TCPN=C32417-000&RQPN=TRF250-180-2 (1 of 4)26/09/2007 12:37:27 •

250-160-2 1 loddet Details - 1 yeo Electronies	
Þ	
Aerospace & Defense	
Appliance	
Automotive	
Communications	
Computer & Consumer Electronics	
Industrial & Commercial	
Instrumentation & Medical Equipment	
By Brand	
A to Z	
• <u>Documentation</u>	<u>n</u>
Find	
Documents & Drawings	
Find CAD Models	
SPICE/Electrical Models	
NAFTA Certificate of Origin	
White Papers	
• <u>Resources</u>	
RoHS	
Compliance & Alternates	
Cross Reference Products	
Compare Multiple Products	
Check Distributor Inventory	
Find Authorized Distributors	
• <u>My Account</u>	
Sign In	
Register	
• <u>Customer</u>	Support
Support	
RoHS Support Center	
Glossary of Terms	
eBulletin Newsletter	
$\underline{\text{Home}} > \underline{\text{Products}} > \underline{\text{By Type}} > \underline{\text{PolyS}}$	Switch Resettable Devices > Product Feature Selector > Product =

TRF250-180-2 Product Details

http://catalog.tycoelectronics.com/TE/bin/TE.Connect?C=1&M=BYPN&TCPN=C32417-000&RQPN=TRF250-180-2 (2 of 4)26/09/2007 12:37:27 •



TRF250-180-2

Raychem Part Number: C32417-000

ĺ	ySwitch Resettable Devices Always EU RoHS/ELV Compliant (Statement of Compliance)
Р	
	Telecom Application
•	• Family Name = TRF250
•	Through Hole Construction
•	• IH (Room Temperature) = .18 Amps.
•	• IT (Room Temperature) = .65 Amps.
	iew all Features

Documentation & Additional Information

Product Drawings:

• TRF250-180 (PDF, English)

Catalog Pages/Data Sheets:

• None Available

Product Specifications:

• None Available

Application Specifications:

• None Available

Instruction Sheets:

• None Available

CAD Files:

• None Available

Additional Information:

• Product Line Information

Related Products:

• Tooling

List all Documents

 $http://catalog.tycoelectronics.com/TE/bin/TE.Connect?C=1\&M=BYPN\&TCPN=C32417-000\&RQPN=TRF250-180-2\ (3\ of\ 4)26/09/2007\ 12:37:27\bullet1000$

Quick Links

- <u>Check</u> <u>Pricing &</u> <u>Availability</u>
- <u>Search for</u> <u>Tooling</u>
- Product
 Feature
 Selector
- <u>Contact Us</u> <u>About This</u>
 - Product

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- UL Recognized = File No. E74889
- Comment = Designed for equipment needing to meet ITU K.20, K.21, K.45 recommendations.

Electrical Characteristics:

- <u>IH (Room Temperature) (Amps.)</u> = 0.18
- <u>IT (Room Temperature) (Amps.)</u> = 0.65
- Vmax Operating (V) = 100
- Rmin() = 0.80
- <u>Rmax ()</u> = 2.200
- R1 Max [Post Trip] (_) = 4.00
- <u>Vmax Interrupt (V rms)</u> = 250
- <u>UL Rated Current (Amps.)</u> = 10
- Tripped Power Dissipation (Typical) (W) = 1.50
- R (Typical) () = 1.50
- UL Rated Voltage (V) = 100

Termination Related Features:

• Construction = Through Hole

Body Related Features:

- Lead Type = Kinked
- CSA File No. = 78165C

Contact Related Features:

• Family Name = TRF250

Configuration Related Features:

• Coating = Coated

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

• <u>Operating Temperature (Max.) ($^{\circ}$ C)</u> = 85

Operation/Application:

• Application = Telecom

Packaging Related Features:

• Packaging Method = Bulk, Tape & Reel

Other:

• Brand = Raychem

<u>Provide Website Feedback | Contact Customer Support</u> <u>Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support</u> © 2007 Tyco Electronics Corporation All Rights Reserved

 $http::/(catalog.tycoelectronics.com/TE/bin/TE.Connect?C=1\&M=BYPN\&TCPN=C32417-000\&RQPN=TRF250-180-2 (4 of 4)26/09/2007 12:37:27 \bullet 1000 (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000)$