



PRODUCT CATALOG
[English](#) [日本語](#)
Catalog

- ▶ [Home](#)
- ▶ [Part Number Search](#)
- ▶ [Document Search](#)
- ▶ [CAD Model Search](#)
- ▶ [Text Search](#)
- ▶ [RoHS/ELV Compliance & Alternates](#)
- ▶ [Multiple Part Comparison](#)
- ▶ [Alphabetical Search](#)
- ▶ [Brand Search](#)
- ▶ [Industry Product Search](#)
- ▶ [Product Type Search](#)
- ▶ [Product Family Search](#)
- ▶ [Competitor Cross Reference](#)
- ▶ [Lead Free Solutions](#)
- ▶ [Tool Search](#)
- ▶ [Help/Glossary](#)

Circuit Protection Devices

↳ PolySwitch Resettable Devices

Raychem SMD100-2018-2

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ▶ General Info ▶ Sales Info 	<ul style="list-style-type: none"> ▶ Pricing ▶ Product Availability 	

Searchable Features:

Brand:	Raychem
RoHS/ELV Compliance:	Not reviewed for ELV/RoHS compliance
Lead Free Solder Process:	Not reviewed for lead free solder process
Vmax Interrupt (V):	0
Construction:	Surface Mount
IH (Room Temperature) (Amps.):	1.1
Rmin (Ω):	0.10
Rmax (Ω):	0.000
R1 Max [Post Trip] (Ω):	0.40

Other Properties:

R (Typical) (Ω):	0.25
IT (Room Temperature) (Amps.):	2.20
UL Rated Voltage (V):	15
UL Rated Current (Amps.):	40
Tripped Power Dissipation (Typical) (W):	1.20
Operating Temperature (Max.) (°C):	85
UL Listed:	File No. E74889
CSA File No.:	78165C
Form Factor (mm):	5050
Form Factor (inches):	2018

[Copyright](#) and [Privacy Statement](#)

Visit [Tyco International, Ltd.](#)

[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)