

[Skip to content](#)

Tyco Electronics Segment

Tyco Electronic

Tyco Electronics commitment to our advant

Search

Dojo Genera

[Home](#) > [Products](#) > [By Type](#) > [PolySwitch Resettable Devices](#) > [Product Feature Selector](#) > [Product Details](#)

MINISMDC160F-2 Product Details

Product P1

Always EU RoHS/ELV Compliant

Always EU RoHS/ELV Compliant

Statement of Compliance

MINISMDC160F-2

Raychem Part Number: 126924000

Part Status is Active

[View all Features](#)

Product Highlights:

- Surface Mount Application
- Family Name = miniSMD
- Surface Mount Construction
- IH (Room Temperature) = 1.6 Amps.
- IT (Room Temperature) = 3.20 Amps.

[View all Features](#)

Quick Link

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

[miniSMD160F](#) (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

None Available

Additional Information:

[Product Line Information](#)

Application Specifications:

None Available

Related Products:

[Tooling](#)

Instruction Sheets:

None Available

CAD Files:

None Available

[List all Documents](#)

Product Features Please use the Product Drawing for all design activity)

Configuration Related Features:

- [Form Factor \(inches\)](#) 1812
- [Form Factor \(mm\)](#) 4532

Product Type Features:

- UL Recognized = 1910 ~~037~~ 4889

Electrical Characteristics:

- [IH \(Room Temperature\) \(Amps\)](#) 1.6
- [IT \(Room Temperature\) \(Amps\)](#) 3.20
- [Vmax Operating \(V\)](#) 9
- [Rmin \(?\)](#) = 0.03
- [R1 Max \[Post Trip\] \(?\)](#) = 0.10
- [UL Rated Current \(Amps\)](#) 100
- Tripped Power Dissipation (Typical) (W) = 0.80

Termination Related Features:

- Construction = Surface Mount

Body Related Features:

- CSA File No. = 1031175 (CA 78185)

Contact Related Features:

- Family Name = miniSMD

Industry Standards:

- [RoHS/ELV Compliance](#) RoHS compliant, ELV compliant
- [Lead Free Solder Process](#) Reflow solder capable 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was Ro compliant
- TUV Certificate No. = R72041438

Conditions for Usage:

- [Operating Temperature \(Max.\)](#) = 85

Operation/Application:

- Application = Surface Mount

Packaging Related Features:

- Packaging Method = Tape & Reel

Other:

- Brand = Raychem