Froducts
 Documentation
 Resources
 My Account
 Customer Support

 Home, > Products, > By Type, > Removable Memory Products, > Product Feature Selector, > Product Details
 \$

 \$

 6/12/2015
 1
 Product Details
 \$

			Live Product Chat Us of 8:30am - 5pm ET, Mon - F
	PC Card (PCMCIA) Conne	ectors &	
	Accessories		
No Image Available	Always EU RoHS/ELV Complia	nt (Statement of Cor	npliance ) <u>Check Pricing &amp;</u> Availability
No image / Wallable	Always EU RUHS/ELV Complia		<u>Search for Tooling</u>
	Product Highlights:		Product Feature
6123215 -1	? Receptacle		<u>Selector</u> Contact Us About
0123213 -1	? CardBus Application		This Product
Active	? Header Type = PC Card Ed Connector	dge	
<u>riouve</u>	Connector 2 Lead Type = Surface Moun	it - Inline	
	leads		
	? Top Side Board Mount		
	<u>View all Features</u>   Fine	<u>d Similar</u>	
	Products_		
Ocumentation & Additi	ional Information		
Product Drawings:			Additional Information:
HARD TRAY ASSY 0.6mm PITCH CARD EDGE CC Incompose)		INECTOR (PDF,	? Product Line Information
Japanese)			
Catalog Pages/Data She	ets:		Related Products: 2 Tooling
None Available			
Product Specifications:			
	Edge Connector (SMT) (1) (P		
? 0.6mm Pitch Card E	Edge Connector (SMT) (2) (P	DF, Japanese)	
Application Specificatio	ns:		
? None Available			
Instruction Sheets:			
? None Available			
7 None Available			
	t & Comprossion Information	\	
CAD Files: (CAD Forma	at & Compression Information	)	
	, Version A)	)	
CAD Files: ( <u>CAD Forma</u> ? <u>2D Drawing</u> (DXF,	, Version A) √ersion A)	)	
CAD Files: ( <u>CAD Forma</u> ? <u>2D Drawing</u> (DXF, ? <u>3D Model</u> (IGES, \	, Version A) √ersion A)	)	
CAD Files: ( <u>CAD Forma</u> ? <u>2D Drawing</u> (DXF, ? <u>3D Model</u> (IGES, \	, Version A) Version A) Version A)	) List all Documents	
CAD Files: ( <u>CAD Forma</u> 2 <u>2D Drawing</u> (DXF, 3 <u>3D Model</u> (IGES, V 3 <u>3D Model</u> (STEP, '	, Version A) Version A) Version A)		
CAD Files: ( <u>CAD Forma</u> ? <u>2D Drawing</u> (DXF, ? <u>3D Model</u> (IGES, V ? <u>3D Model</u> (STEP, '	, Version A) Version A) Version A)	List all Documents	-
CAD Files: (CAD Forma ? 2D Drawing (DXF, ? <u>3D Model</u> (IGES, V ? <u>3D Model</u> (STEP, ' Product Features (Plear Product Type Features:	, Version A) Version A) Version A) se use the Product Drawing for all design activity)	List all Documents	
CAD Files: (CAD Forma ? 2D Drawing (DXF, ? <u>3D Model</u> (IGES, V ? <u>3D Model</u> (STEP, V Product Features (Please Product Type Features: ? Product Type _ = Re	, Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle	List all Documents Housing Related	Features: I Features: Iterial = Liquid Crystal Polymer
CAD Files: (CAD Forma 2 D Drawing (DXF, 3 <u>3D Model</u> (IGES, V 3 <u>3D Model</u> (STEP, V Product Features (Pleas Product Type Features: 2 Product Type _ = R( 3 Number of Positions)	, Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle s = 150	List all Documents Housing Related ? Housing Ma (LCP)	aterial = Liquid Crystal Polymer
CAD Files: (CAD Forma 2 D Drawing (DXF, 3D Model (IGES, V 3D Model (STEP, V 3D Model (STEP, V Product Features (Please Product Type Features: 2 Product Type = R( 3 Number of Positions 3 Mount Angle = Ve	, Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle s = 150	List all Documents Housing Related ? Housing Ma (LCP)	
CAD Files: (CAD Forma 2 D Drawing (DXF, 3 <u>3D Model</u> (IGES, V 3 <u>3D Model</u> (STEP, V <b>Product Features</b> <b>Product Type Features</b> : Product Type Features: Product Type = Ref Number of Positions Mount Angle = Ve Shielded = No	, Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle s = 150 ertical	List all Documents Housing Related <sup>2</sup> Housing Ma (LCP) <sup>3</sup> Housing Fla	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0
CAD Files: (CAD Forma 2 D Drawing (DXF, 3 <u>3D Model</u> (IGES, V 3 <u>3D Model</u> (STEP, V Product Features (Please Product Type Features: 2 Product Type = R( 3 Number of Positions 3 Mount Angle = Ve	, Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle s = 150 ertical	List all Documents Housing Related 7 Housing Ma (LCP) 7 Housing Fla Industry Standar	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0
CAD Files: (CAD Forma ? 2D Drawing (DXF, ? 3D Model (IGES, V ? 3D Model (STEP, ' ? 3D Model (STEP, ' Product Features: Product Type Features: ? Product Type = RG ? Number of Positions ? Mount Angle = Ve ? Shielded = No ? Mating Polarization	, Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle s = 150 ertical = Without	List all Documents Housing Related ? Housing Ma (LCP) ? Housing Fla Industry Standar ? RoHS/ELV compliant	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV
CAD Files: (CAD Forma ? 2D Drawing (DXF, ? 3D Model (IGES, V ? 3D Model (STEP, V ? 3D Model (STEP, V Product Features: Product Type Features: ? Product Type = R( ? Number of Positions ? Mount Angle = Ve ? Shielded = No ? Mating Polarization	, Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle s = 150 errtical = Without	List all Documents Housing Related ? Housing Ma (LCP) ? Housing Fla Industry Standar ? RoHS/ELV compliant ? Lead Free S	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder
CAD Files: (CAD Forma ? 2D Drawing(DXF, ? 3D Model_ (IGES, V ? 3D Model_ (IGES, V ? 3D Model_ (STEP, V Product Features Product Type Features: ? Product Type _= R( ? Number of Position ? Mount Angle_ = Ve ? Shielded_ = No ? Mating Polarization Mechanical Attachment:	, Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle s = 150 errtical = Without	List all Documents Housing Related ? Housing Ma (LCP) ? Housing Fla Industry Standar ? ROHS/ELV compliant ? Lead Free S capable to 2	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV
CAD Files: (CAD Forma ? 2D Drawing_(DXF, ? 3D Model_(IGES, V ? 3D Model_(IGES, V ? 3D Model_(STEP, ' Product Features) ? Product Type Features: ? Product Type Features: ? Product Type Features: ? Number of Positions ? Mount Angle_= Ve ? Shielded_= No ? Mating Polarization Mechanical Attachment: ? Board Mount_= To Termination Related Features	, Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle s = 150 ertical = Without : pp Side atures:	List all Documents Housing Related ? Housing Ma (LCP) ? Housing Fla Industry Standar ? RoHS/ELV compliant ? Lead Free S capable to 2 260°C	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder 245°C, Reflow solder capable to
CAD Files: (CAD Forma ? 2D Drawing(DXF, ? 3D Model_ (IGES, V ? 3D Model_ (IGES, V ? 3D Model_ (STEP, ' Product Features: ? Product Type Features: ? Product Type = R( ? Number of Positions ? Mount Angle_ = Ve ? Shielded_ = No ? Mating Polarization Mechanical Attachment: ? Board Mount_ = To	, Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle s = 150 ertical = Without : pp Side atures:	List all Documents Housing Related ? Housing Ma (LCP) ? Housing Fla Industry Standar ? RoHS/ELV compliant ? Lead Free S capable to 2 260°C	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder 245°C, Reflow solder capable to Compliance History = Always was
CAD Files: (CAD Forma ? 2D Drawing_(DXF, ? 3D Model_(IGES, V ? 3D Model_(IGES, V ? 3D Model_(STEP, ' Product Type Features: ? Product Type Features: ? Product Type Features: ? Number of Positions ? Mount Angle_ = Ve ? Shielded_ = No ? Mating Polarization Mechanical Attachment: ? Board Mount_ = To Termination Related Feat ? Solder Tail Contact	, Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle s = 150 ertical = Without : pp Side atures:	List all Documents Housing Related <sup>9</sup> Housing Ma (LCP) <sup>9</sup> Housing Fla Industry Standar <sup>9</sup> ROHS/ELV compliant <sup>9</sup> Lead Free S capable to 2 260°C <sup>9</sup> ROHS/ELV	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder 245°C, Reflow solder capable to Compliance History = Always was bliant
CAD Files: (CAD Forma ? 2D Drawing(DXF, ? 3D Model_(IGES, V ? 3D Model_(IGES, V ? 3D Model_(STEP, V Product Type Features: ? Product Type = Ret ? Number of Positions ? Mount Angle_ = Ve ? Shielded_ = No ? Mating Polarization Mechanical Attachment: ? Board Mount_ = To Termination Related Features: Body Related Features:	, Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle s = 150 errtical = Without : pp Side atures: Plating = Gold Flash	List all Documents Housing Related P Housing Ma (LCP) Housing Flated Industry Standar ROHS/ELV compliant Lead Free S capable to 2 260°C ROHS/ELV ROHS comp Height = State	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder 245°C, Reflow solder capable to Compliance History = Always was bliant andard
CAD Files: (CAD Forma ? 2D Drawing(DXF, ? 3D Model_(IGES, V ? 3D Model_(IGES, V ? 3D Model_(STEP, V Product Type Features: ? Product Type = RC ? Number of Position ? Mount Angle_ = Ve ? Shielded_ = No ? Mating Polarization Mechanical Attachment: ? Board Mount_ = To Fermination Related Features: ? Header Type_ = PC	, Version A) Version A) Version A) Se use the Product Drawing for all design activity) ecceptacle s = 150 errtical = Without : pp Side atures: Plating = Gold Flash C Card Edge Connector	List all Documents Housing Related <sup>7</sup> Housing Ma (LCP) <sup>9</sup> Housing Fla Industry Standar <sup>7</sup> RoHS/ELV compliant <sup>9</sup> Lead Free S capable to 2 260°C <sup>9</sup> RoHS/ELV RoHS comp <sup>9</sup> Height = Sta Operation/Applic	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder 245°C, Reflow solder capable to Compliance History = Always was pliant andard cation:
CAD Files: (CAD Forma ? 2D Drawing(DXF, ? 3D Model_(IGES, V ? 3D Model_(IGES, V ? 3D Model_(STEP, V Product Features (Please Product Type Features: ? Product Type Features: ? Product Type Features: ? Number of Positions ? Number of Positions ? Mount Angle = Ve ? Shielded = No ? Mating Polarization Mechanical Attachment: ? Board Mount _= To Termination Related Features: ? Solder Tail Contact Body Related Features: ? Header Type _= Surfa	, Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle s = 150 errtical = Without : pp Side atures: Plating = Gold Flash C Card Edge Connector ace Mount - Inline leads	List all Documents Housing Related P Housing Ma (LCP) Housing Flated Industry Standar ROHS/ELV compliant Lead Free S capable to 2 260°C ROHS/ELV ROHS comp Height = State	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder 245°C, Reflow solder capable to Compliance History = Always was pliant andard cation:
CAD Files: (CAD Forma ? 2D Drawing(DXF, ? 3D Model_(IGES, V ? 3D Model_(IGES, V ? 3D Model_(STEP, V Product Type Features: ? Product Type _= RC ? Number of Position ? Mount Angle_ = Ve ? Shielded_ = No ? Mating Polarization Mechanical Attachment: ? Board Mount_ = To Termination Related Features: ? Header Type_ = PC	, Version A) Version A) Version A) Secure the Product Drawing for all design activity) ecceptacle S = 150 errtical = Without : pp Side atures: Plating = Gold Flash C Card Edge Connector ace Mount - Inline leads = Double	List all Documents Housing Related Phousing Ma (LCP) Housing Flated Industry Standar RoHS/ELV compliant Lead Free Standar Capable to 2 260°C RoHS/ELV RoHS comp Height = Standar Operation/Applic Application	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder 245°C, Reflow solder capable to Compliance History = Always was pliant andard cation: _ = CardBus
CAD Files: (CAD Forma ? 2D Drawing(DXF, ? 3D Model_(IGES, V ? 3D Model_(IGES, V ? 3D Model_(STEP, V Product Type Features: ? Product Type Features: ? Product Type = Re ? Number of Positions ? Mount Angle_ = Ve ? Shielded_ = No ? Mating Polarization Mechanical Attachment: ? Board Mount_ = To Vechanical Attachment: ? Board Mount_ = To Fermination Related Features: ? Older Tail Contact Body Related Features: ? Header Type_ = PC ? Lead Type_ = Surfa ? Single/Double Slot	, Version A) Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle $s_{_}$ = 150 errtical = Without merrical = Without C Card Edge Connector ace Mount - Inline leads = Double merctor = Both	List all Documents Housing Related <sup>2</sup> Housing Ma (LCP) <sup>3</sup> Housing Fla Industry Standar <sup>3</sup> ROHS/ELV compliant <sup>3</sup> Lead Free S capable to 2 260°C <sup>3</sup> ROHS/ELV ROHS comp <sup>3</sup> Height = Sta Operation/Applic <sup>3</sup> Application Packaging Related	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder 245°C, Reflow solder capable to Compliance History = Always was bliant andard <b>:ation:</b> _ = CardBus <b>ed Features:</b>
CAD Files: (CAD Forma 2 D Drawing(DXF, 3D Model_(IGES, V 3D Model_(IGES, V 3D Model_(STEP, V Product Features Product Type Features: Product Type Features: Product Type Features: Number of Positions Mount Angle = Ve Shielded = No Mating Polarization Mechanical Attachment: Board Mount _= To Termination Related Features: Solder Tail Contact Body Related Features: Header Type _= Surfa Single/Double Slot Slot Containing Cor	, Version A) Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle $s_{_}$ = 150 errtical = Without merrical = Without C Card Edge Connector ace Mount - Inline leads = Double merctor = Both	List all Documents Housing Related <sup>2</sup> Housing Ma (LCP) <sup>3</sup> Housing Fla Industry Standar <sup>2</sup> ROHS/ELV compliant <sup>3</sup> Lead Free S 260°C <sup>3</sup> ROHS/ELV ROHS comp <sup>4</sup> Height = Sta Operation/Applic <sup>2</sup> Application Packaging Relate	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder 245°C, Reflow solder capable to Compliance History = Always was bliant andard <u>cation:</u> _ = CardBus <u>ed Features:</u> <u>Method</u> = Tray
CAD Files: (CAD Forma ? 2D Drawing_ (DXF, ? 3D Model_ (IGES, V ? 3D Model_ (IGES, V ? 3D Model_ (STEP, ' Product Type Features: ? Product Type Features: ? Product Type Features: ? Product Type Features: ? Number of Positions ? Mount Angle_ = Ve ? Shielded_ = No ? Mating Polarization Mechanical Attachment: ? Board Mount_ = To Termination Related Features: ? Header Type_ = PC ? Lead Type_ = Surfa ? Single/Double Slot ? Solt Containing Cor ? Centerline (mm [in]) Contact Related Features	, Version A) Version A) Version A) Se use the Product Drawing for all design activity) ecceptacle S = 150 ertical = Without : pp Side atures: Plating = Gold Flash C Card Edge Connector ace Mount - Inline leads = Double onector = Both ) = 0.60 [0.024]	List all Documents Housing Related <sup>2</sup> Housing Ma (LCP) <sup>3</sup> Housing Fla Industry Standar <sup>3</sup> ROHS/ELV compliant <sup>3</sup> Lead Free S capable to 2 260°C <sup>3</sup> ROHS/ELV ROHS comp <sup>3</sup> Height = Sta Operation/Applic <sup>3</sup> Application Packaging Related	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder 245°C, Reflow solder capable to Compliance History = Always was bliant andard <u>cation:</u> _ = CardBus <u>ed Features:</u> <u>Method</u> = Tray
CAD Files: (CAD Forma 2 D Drawing(DXF, 3 D Model_ (IGES, V 3 D Model_ (IGES, V 3 D Model_ (STEP, V 2 3D Model_ (STEP, V 2 3D Model_ (STEP, V 2 9 Product Type Features: 2 9 Product Type = RC 2 Number of Positions 2 Mount Angle_ = Ve 3 Shielded_ = No 2 Mating Polarization Mechanical Attachment: 2 Board Mount_ = To Mechanical Attachment: 2 Board Mount_ = To Termination Related Features: 2 Header Type_ = PC 3 Lead Type_ = Surfa 3 Single/Double Slot. 3 Slot Containing Cor 3 Centerline (mm [in]) Contact Related Features 2 Contact Mating Area	, Version A) Version A) Version A) Se use the Product Drawing for all design activity) ecceptacle S = 150 ertical = Without S = Without S = Without S = Without S = Cold Flash C Card Edge Connector ace Mount - Inline leads = Double nnector = Both ) = 0.60 [0.024]	List all Documents Housing Related <sup>2</sup> Housing Ma (LCP) <sup>3</sup> Housing Fla Industry Standar <sup>2</sup> ROHS/ELV compliant <sup>3</sup> Lead Free S 260°C <sup>3</sup> ROHS/ELV ROHS comp <sup>4</sup> Height = Sta Operation/Applic <sup>2</sup> Application Packaging Relate	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder 245°C, Reflow solder capable to Compliance History = Always was bliant andard <u>cation:</u> _ = CardBus <u>ed Features:</u> <u>Method</u> = Tray
CAD Files: (CAD Forma ? 2D Drawing(DXF, ? 3D Model_ (IGES, V ? 3D Model_ (IGES, V ? 3D Model_ (STEP, V Product Features: ? Product Type Features: ? Product Type Features: ? Number of Position ? Mount Angle_ = Ve ? Shielded = No ? Mount Angle_ = Ve ? Shielded = No ? Mating Polarization Mechanical Attachment: ? Board Mount_ = To Termination Related Features: ? Header Type_ = PC ? Lead Type_ = Surfa ? Single/Double Slot ? Slot Containing Cor ? Centerline (mm [in]) Contact Related Features: ? Contact Mating Area Flash	, Version A) Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle S = 150 errical = Without : pp Side atures: Plating = Gold Flash C Card Edge Connector ace Mount - Inline leads = Double nnector = Both ) = 0.60 [0.024] SS: a Plating Material = Gold	List all Documents Housing Related 7 Housing Ma (LCP) 7 Housing Fla Industry Standar 7 RoHS/ELV compliant 7 Lead Free S capable to 2 260°C 7 RoHS/ELV RoHS comp 7 Height = Sta Operation/Applic 7 Application Packaging Relate 7 Packaging C	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder 245°C, Reflow solder capable to Compliance History = Always was bliant andard <u>sation:</u> _ = CardBus <u>ed Features:</u> <u>Method</u> = Tray Quantity = 30
CAD Files: (CAD Forma ? 2D Drawing(DXF, ? 3D Model_ (IGES, V ? 3D Model_ (IGES, V ? 3D Model_ (STEP, V Product Type Features: ? Product Type Features: ? Product Type = Re ? Number of Position ? Mount Angle_ = Ve ? Shielded_ = No ? Mount Angle_ = Ve ? Shielded_ = No ? Mount Angle_ = Ve ? Shielded_ = No ? Mating Polarization Mechanical Attachment: ? Board Mount_ = To Mechanical Attachment: ? Board Mount_ = To Termination Related Features: ? Header Type_ = PC ? Lead Type_ = Surfa ? Slot Containing Cor ? Centerline (mm [in]) Contact Related Features ? Contact Mating Area Flash ? Region = Americas,	, Version A) Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle s = 150 errtical = Without : pp Side atures: Plating = Gold Flash C Card Edge Connector ace Mount - Inline leads = Double nnector = Both ) = 0.60 [0.024] es: a Plating Material = Gold , Asia/Pacific	List all Documents Housing Related Provide the Housing Mar (LCP) Housing Flater Housing Flater Houstry Standar RoHS/ELV compliant Lead Free S capable to 2 260°C RoHS/ELV RoHS comp Height = Stater Operation/Application Packaging Relater Packaging ( Other:	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder 245°C, Reflow solder capable to Compliance History = Always was bliant andard <u>sation:</u> _ = CardBus <u>ed Features:</u> <u>Method</u> = Tray Quantity = 30
CAD Files: (CAD Forma ? 2D Drawing(DXF, ? 3D Model_ (IGES, V ? 3D Model_ (IGES, V ? 3D Model_ (STEP, V Product Features: ? Product Type Features: ? Product Type = Re ? Number of Position ? Mount Angle_ = Ve ? Shielded_ = No ? Mount Angle_ = Ve ? Shielded_ = No ? Mating Polarization Mechanical Attachment: ? Board Mount_ = To Termination Related Features: ? Header Type_ = PC ? Lead Type_ = Surfa ? Single/Double Slot ? Slot Containing Cor ? Centerline (mm [in]) Contact Related Features: ? Contact Mating Area Flash	, Version A) Version A) Version A) Version A) se use the Product Drawing for all design activity) ecceptacle S = 150 ertical = Without : pp Side atures: Plating = Gold Flash C Card Edge Connector ace Mount - Inline leads = Double onector = Both ) = 0.60 [0.024] es: a Plating Material = Gold , Asia/Pacific Copper Alloy	List all Documents Housing Related Provide the Housing Mar (LCP) Housing Flater Housing Flater Houstry Standar RoHS/ELV compliant Lead Free S capable to 2 260°C RoHS/ELV RoHS comp Height = Stater Operation/Application Packaging Relater Packaging ( Other:	aterial = Liquid Crystal Polymer ammability Rating = UL 94V -0 rds: <u>Compliance</u> = RoHS compliant, ELV <u>Solder Processes</u> = Reflow solder 245°C, Reflow solder capable to Compliance History = Always was bliant andard <u>sation:</u> _ = CardBus <u>ed Features:</u> <u>Method</u> = Tray Quantity = 30

Provide Website Feedback | Contact Customer Support