

1734451 -2 Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



1734451 -2

[Active](#)

Removable Memory Products

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- ? Number of Positions = 50
- ? Format = CompactFlash™
- ? CompactFlash™ Product Type = Header Only
- ? Header Type = Type I, Type II
- ? Lead Type = Surface Mount - Inline leads

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [PIN HEADER SLIM TYPE, 50 POS, TOP BOARD, COMPACT FLA...](#) (PDF, Japanese)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? [COMPACT FLASH CARD, 1.27mm\(.050"\) PITCH](#) (PDF, English)

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files: ([CAD Format & Compression Information](#))

- ? [2D Drawing](#) (DXF, Version B)
- ? [3D Model](#) (IGES, Version B)
- ? [3D Model](#) (STEP, Version B)

[List all Documents](#)

Related Products:

- ? [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? [Number of Positions](#) = 50
- ? Mount Angle = Right Angle
- ? Holddowns = With
- ? Shielded = No
- ? Color = White

Mechanical Attachment:

- ? Mounting Style = Top (Printed Circuit Board)

Termination Related Features:

- ? Solder Tail Contact Plating = Tin

Body Related Features:

- ? CompactFlash™ Product Type = Header Only
- ? Header Type = Type I, Type II
- ? Lead Type = Surface Mount - Inline leads
- ? Number of Rows = Dual
- ? Centerline (mm [in]) = 1.27 [0.050]

Contact Related Features:

- ? Contact Mating Area Plating Material = Gold (30)
- ? Vacuum Tape = Without
- ? Region = Americas
- ? Contact Material = Brass
- ? Contact Underplating = Nickel

Housing Related Features:

- ? Housing Material = Thermoplastic
- ? Housing Flammability Rating = UL 94V -0

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- ? Format = CompactFlash™

Packaging Related Features:

- ? Packaging Method = Tray

Other:

- ? Brand = AMP