

# 1/4" x 1/4" to 1 1/4" In-Line Fuse Holders

## **HHB Series**

#### Description

- For ¼" x %" to ¼" x 1 ¼" fuses
- Accepts #16 to #12 AWG copper wire
- · Simple crimp assembly
- · "Snap-Lock" feature provides strong positive union
- High visibility yellow color
- · Recommended crimp tools:
  - Thomas & Betts ERG-2001
  - Channelock No. 909
  - General Electric U.S. & Metric Electrical Terminal Tool
- UL flammability rating 94 V2

## **Environmental Data**

 Pull Force: 5 pounds minimum to separate fuseholder housing with fuse inside

#### **Ordering**

Specify packaging code

Insert packaging code prefix before part number.
E.g. BK/HHB-R


Specify option codes if desired

• Drop "-R" suffix when ordering. E.g. BK/HHB-Y408

Specifications		
Part	-	
Number	Volts	Amps
HHB-R*	32	30 max


<sup>\*</sup>RoHS compliant construction.





### Dimensions - in (mm)

Drawing Not to Scale



Fuse Length	"L" with fuse installed
7/8"	2.100 Max.
1"	2.250 Max.
11/4"	2.420 Max.

Component	Material
Body	Nylon
Crimp	Copper Tin-Plated

Packaging Code				
Packaging Code Prefix	Description			
Blank	10 fuse holders packed into a carton			
BK	1,000 fuse holders packed into a cardboard shelf package			

Option Code		
Option Code	Description	
Y408**†	#14 AWG insulated wire with 8 inch yellow leads	
R408 <sup>†</sup>	#14 AWG insulated wire with 8 inch red leads	
B408** <sup>†</sup>	#14 AWG insulated wire with 8 inch black leads	
Y419**†	#14 AWG insulated wire with 19 inch yellow leads	
R419** <sup>†</sup>	#14 AWG insulated wire with 19 inch red leads	
B419** <sup>†</sup>	#14 AWG insulated wire with 19 inch black leads	

<sup>\*\*</sup>Not available in RoHS compliant construction.

The only controlled copy of this Data Sheet is the electronic read-only version located on the Cooper Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Cooper Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Cooper Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Life Support Policy: Cooper Bussmann does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

© 2009 Cooper Bussmann St. Louis, MO 63178 www.cooperbussmann.com







Data Sheet 2103



0509 BU-SB09721 Page 1 of 1

<sup>†</sup> Drop "-R" suffix when ordering these options.