AGRF800 Product Details - Tyco Electronics

Skip to content

Corporate Home | ▶ Electronic Components | Segments | Who We Are

Worldwide





Our commitment. Your advantage.

Search By:



Sign In | Register (Why Register?)

Products

Þ

Connectors

Electromechanical

Components

**Electronic Modules** 

Fiber Optics

Filters

Identification Labeling

Products

Passive Components

Power Sources

RF & Microwave Products

**Tooling Products** 

Touch Screen Displays

Tubing, Molded and

Harnessing Products

Wire, Cable and Cable

Assemblies

List all Product Types



 $\underline{Home} > \underline{Products} > \underline{By\ Type} > \underline{PolySwitch\ Resettable\ Devices} > \underline{Product\ Feature\ Selector} > \underline{Product\ Details}$ 

# **AGRF800 Product Details**



### AGRF800

Raychem Part Number: A95482-000 **Active** 

## **PolySwitch Resettable Devices**



Always EU RoHS/ELV Compliant (Statement of Compliance)

### **Product Highlights:**

- Automotive, Radial Application
- Family Name = AGRF
- Radial Construction, Through Hole Construction
- IH (Room Temperature) = 8 Amps.
- IT (Room Temperature) = 15.00 Amps.

View all Features

### Quick Links

- Check Pricing & Availability
- Search for **Tooling**
- Product Feature Selector
- Contact Us **About This** Product

### **Documentation & Additional Information**

### **Product Drawings:**

• AGRF800 (PDF, English)

### **Catalog Pages/Data Sheets:**

• None Available

# **Product Specifications:**

• None Available

# **Application Specifications:**

• None Available

### **Instruction Sheets:**

• None Available

# **CAD Files:**

• None Available

# **Additional Information:**

• Product Line Information

### **Related Products:**

Tooling

List all Documents

### Product Features (Please use the Product Drawing for all design activity)

#### **Product Type Features:**

• UL Recognized = File No. E74889

#### **Electrical Characteristics:**

- IH (Room Temperature) (Amps.) = 8
- IT (Room Temperature) (Amps.) = 15.00
- <u>Vmax Operating (V)</u> = 16
- Rmin() = 0.0049
- Rmax() = 0.0113
- <u>R1 Max [Post Trip] ( )</u> = 0.0175
- <u>UL Rated Current (Amps.)</u> = 100
- Tripped Power Dissipation (Typical) (W) = 3.20
- RA Max ( ) = 0.0181

#### **Termination Related Features:**

• Construction = Radial, Through Hole

### **Body Related Features:**

- Lead Type = Bottle Kink
- CSA File No. = 78165C

### **Contact Related Features:**

• Family Name = AGRF

### **Configuration Related Features:**

• Coating = Coated

#### **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

#### **Conditions for Usage:**

• Operating Temperature (Max.) ( $^{\circ}$ C) = 85

#### **Operation/Application:**

• Application = Automotive, Radial

#### **Packaging Related Features:**

• Packaging Method = Bulk

#### Other:

• Brand = Raychem

<u>Provide Website Feedback | Contact Customer Support</u>

<u>Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support</u>

© 2007 Tyco Electronics Corporation All Rights Reserved