


ADSL LINE TRANSFORMERS

For Centillium's CopperFlite™ 8-Port CO Chipsets



- Matched to Centillium's CopperFlite™ CT-L53SC08, CT-L63SC08, and CT-L73SC08 chipsets
- Excellent THD performance in a small footprint
- Designed to meet UL 1950 and EN 60950 supplementary insulation requirements for working voltages up to 250Vrms

Electrical Specifications @ 25°C — Operating Temperature -40°C to +85°C

Part Number	Mounting	ADSL CO Termination	Turns Ratio (Chip:Line) (±2%)	Inductance (@ 100mV)	Leakage Inductance (@ 100kHz, 0.1Vrms)
BX2347	THT	Active	1CS:1CS	850µH ±7% @ 30kHz (1-4) with (2-3) shorted	5.5µH MAX (1-4) with (2-3), (7-10) and (8-9) shorted
BX2348 ¹	SMT				
BX2349 ¹	SMT	Passive	1CS:1.8CS		
BX2380	THT				


Additional Specifications

Part Number	THD (dB @ 100Ω)	Longitudinal Balance (dB)	DC Resistance		Isolation Voltage
BX2347	≤-80 (@40kHz, 2.5Vrms)	≤-50 (@10kHz, 1.1Vrms)	≤1.40Ω	≤1.40Ω	1500Vrms (60 sec)
BX2348 ¹			(1-4) with (2-3) shorted	(7-10) with (8-9) shorted	
BX2349 ¹			≤1.30Ω	≤0.75Ω	
BX2380			(1-4) with (2-3) shorted	(7-10) with (8-9) shorted	


¹Transformers are shipped in tubes unless tape and reel is specified. Please add the suffix "T" (i.e. BX2348T) for tape and reel orders.

Mechanicals

BX2347/BX2380




BX2348/BX2349



	BX2347/BX2380	BX2348/BX2349
Weight6.2 grams6.2 grams
Tape & ReelN/A150/reel
Tray/Tube65/tray60/tray
Dimensions:	Inches	mm
	Unless otherwise specified, all tolerances are ± .010 / 0,25	

Schematic



For More Information:

Pulse Worldwide Headquarters

12220 World Trade Drive
San Diego, CA 92128
U.S.A.
www.pulseeng.com
TEL: 858 674 8100
FAX: 858 674 8262

Pulse Northern Europe

3 Huxley Road
Surrey Research Park
Guildford, Surrey GU2 5RE
United Kingdom
TEL: 44 1483 401700
FAX: 44 1483 401701

Pulse Southern Europe

Zone Industrielle
F-39270
Orgelet
France
TEL: 33 3 84 35 04 04
FAX: 33 3 84 25 46 41

Pulse China Headquarters

No. 1
Industrial District
Changan, Dongguan
China
TEL: 86 769 5538070
FAX: 86 769 5538870

Pulse North China

Room 1002
No. 819
Nanjing West Rd
Shanghai
China
TEL: 86 21 32181071
FAX: 86 21 32181396

Pulse South Asia

150 Kampong Ampat
#07-01/02
KA Centre
Singapore 368324
TEL: 65 6287 8998
FAX: 65 6280 0080

Pulse North Asia

3F-4, No. 81, Sec. 1
Hsin Tai Wu Road
Hsi-Chih
Taipei Hsien
Taiwan
TEL: 886 2 26980228
FAX: 886 2 26980948

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.

© Copyright, 2005. Pulse Engineering, Inc. All rights reserved.

www.pulseeng.com

B994.B (12/05)