



MATERIAL: HOUSING - NYLON MOLDING COMPOUND, 94V-0, GLASS FILLED, BLACK.
 TERMINALS - 0.25 [.010] THICK BRASS PLATED WITH 0.254 MICRONS [.00010] MINIMUM THICK GOLD OVER 1.016 MICRONS [.00040] MINIMUM THICK PALADIUM NICKEL OVER 0.05 MICRONS [.00002] MINIMUM THICK GOLD IN CONTACT AREAS AND 3.8 MICRONS [.000150] MINIMUM THICK TIN ON SOLDER TINES OVER 2.54 MICRONS [.000100] MINIMUM THICK NICKEL UNDERPLATE.
 SHIELD - STAINLESS STEEL, TIN PLATED STRIKER PLATE - STAINLESS STEEL.

2. PACKAGED IN TAPE AND REEL.

KEY 5-15	5-5558556-5
KEY 4-15	5-5558556-4
KEY 3-15	5-5558556-3
KEY 2-15	5-5558556-2
KEY 1-15	5-5558556-1
KEYING OPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT		DESIGNED BY	REVIEWED BY	DATE	BY	CHK	APP
INCHES	NO DIMENSIONAL TOLERANCES	J. J. MCMANUS	W. J. COLEMAN	11/15/68			
DEC	DEC	DEC	DEC	DEC	DEC	DEC	DEC
APR	APR	APR	APR	APR	APR	APR	APR
MAY	MAY	MAY	MAY	MAY	MAY	MAY	MAY
SEP	SEP	SEP	SEP	SEP	SEP	SEP	SEP
NOV	NOV	NOV	NOV	NOV	NOV	NOV	NOV
MATERIAL		WEIGHT	SEE	DATE	DRAWING NO.	REVISED TO	
CUTTING					A1 00779	5-5558556	
CUSTOMER DRAWING							

