




(2,00mm) .0787"

FCT, EMT SERIES



# FLEXCARD™ TERMINAL & SOCKET STRIPS

Mates with:  
EMT

## SPECIFICATIONS

For complete specifications and recommended PCB layouts see [www.samtec.com?FCT](http://www.samtec.com?FCT)

**Insulator Material:**  
Black Liquid Crystal Polymer



**Terminal Material:**  
Phosphor Bronze

**Current Rating:**  
3A @ 80°C ambient

**Operating Temp Range:**  
-55°C to +105°C with Tin;  
-55°C to +125°C with Gold

**Plating:**  
Sn or Au over  
50µ" (1,27µm) Ni

**RoHS Compliant:**  
Yes

**Processing:**  
Lead-Free Solderable:  
Wave, or reflow with  
Matte Sn plating

**Note:** Some lengths, styles and options are non-standard, non-returnable.

<b>FCT</b>	<b>1</b>	<b>NO. PINS PER ROW</b>	<b>LEAD STYLE</b>	<b>PLATING OPTION</b>	<b>D</b>	<b>CARD SLOT</b>	<b>TAIL OPTION</b>	<b>SL</b>									
		<b>20, 30 &amp; 40</b> (Call Samtec for other sizes)	<b>Specify LEAD STYLE from chart</b>	<p><b>-F</b> = Gold flash on post, Matte Tin on tail</p> <p><b>-L</b> = 10µ" (0,25µm) Gold on post, Matte Tin on tail</p> <p><b>-S</b> = 30µ" (0,76µm) Gold on post, Matte Tin on tail</p>		<b>-01</b> = Accepts (0,80mm) .031" thick card	<b>-RA</b> = Right Angle (Leave blank for vertical version. Style -02 only)										
		<p>No. of positions x (2,00) .0787 + (18,19) .716</p> <p>No. of positions x (2,00) .0787 + (13,87) .546</p>		<p>(2,00) .0787</p> <p>(3,20) .126</p> <p>(2,00) .0787</p> <p>(44,45) 1.750</p>		<p>(2,00) .0787</p> <p>(2,29) .090</p> <p>(38,10) 1.500</p> <p>(1,14) .045</p> <p>(1,52) .060 TYP</p> <p>(2,54) .100 DIA TYP</p>		<table border="1"> <thead> <tr> <th>LEAD STYLE</th> <th>Y</th> <th>CARD-TO-BOARD SPACE (X)</th> </tr> </thead> <tbody> <tr> <td>-02</td> <td>(6,35) .250</td> <td>(2,60) .1025</td> </tr> <tr> <td>-03</td> <td>(9,53) .375</td> <td>(5,78) .2275</td> </tr> </tbody> </table>	LEAD STYLE	Y	CARD-TO-BOARD SPACE (X)	-02	(6,35) .250	(2,60) .1025	-03	(9,53) .375	(5,78) .2275
LEAD STYLE	Y	CARD-TO-BOARD SPACE (X)															
-02	(6,35) .250	(2,60) .1025															
-03	(9,53) .375	(5,78) .2275															
		<p>(88,10) 1.500</p> <p>Y</p> <p>X</p>		<p>(2,00) .0787</p> <p>(2,29) .090</p> <p>(3,81) .150</p> <p>(2,00) .0787</p>		<p>(2,00) .0787</p> <p>(2,29) .090</p> <p>(38,10) 1.500</p> <p>(1,14) .045</p> <p>(1,52) .060 TYP</p> <p>(2,54) .100 DIA TYP</p>											
		<p>Style -02</p> <p>Style -03</p>		<p>-RA OPTION</p>													

## SPECIFICATIONS

For complete specifications and recommended PCB layouts see [www.samtec.com?EMT](http://www.samtec.com?EMT)

**Insulator Material:**  
Black LCP



**Contact Material:**  
BeCu

**Current Rating:**  
3A @ 80°C ambient

**Operating Temp Range:**  
-55°C to +125°C

**Plating:**  
Sn or Au over  
50µ" (1,27µm) Ni

**Contact Resistance:**  
10 mΩ max

**Insertion Depth:**  
(3,05mm) .120" to  
(3,30mm) .130"

**Insertion Force:**  
-01=1.5oz (0,44N) average  
-51=2.5oz (0,70N) average

**Withdrawal Force:**  
-01=1.1oz (0,31N) average  
-51=1.5oz (0,44N) average

**Lead-Free Solderable:**  
Yes, with Matte Sn plating

**SMT Lead Coplanarity:**  
(0,10mm) .004" max (20)  
(0,15mm) .006" max (30-40)

**RoHS Compliant:**  
Yes

<b>EMT</b>	<b>1</b>	<b>NO. PINS PER ROW</b>	<b>CARD THICKNESS</b>	<b>PLATING OPTION</b>	<b>D</b>
		<b>20, 30, 40</b> (Call Samtec for other sizes)	<p><b>-01</b> = (0,80mm) .031" thick board (Low Insertion Force)</p> <p><b>-51</b> = (0,80mm) .031" thick board (Standard Insertion Force)</p>	<p><b>-L</b> = 10µ" (0,25µm) Gold on contact, Matte on tail</p> <p><b>-S</b> = 30µ" (0,76µm) Gold on contact, Matte Tin on tail</p>	
		<p>No. of positions x (2,00) .0787 + (3,56) .140</p>		<p>(2,08) .082</p> <p>(2,00) .0787</p> <p>(2,00) .0787</p> <p>(4,00) .158</p>	
		<p>(5,46) .215</p> <p>(0,51) .020</p> <p>(3,56) .140</p>		<p>(2,74) .108</p> <p>(0,81) .032</p>	



Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC SILICON VALLEY • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329  
 SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0  
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 8890337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292 SAMTEC ISRAEL • Tel: 972-3-7526600  
 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-61103766 SAMTEC TAIWAN • Tel: 886-2-2735-6109  
 Downloaded from [Elcodis.com](http://Elcodis.com) electro SAMTEC HONG KONG • Tel: 852-2600-9858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9512 7747 SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112