


(1,27mm) .050"
FCF, EMF SERIES

FLEXCARD™ TERMINAL & SOCKET STRIPS

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?FCF

Insulator Material: Black Liquid Crystal Polymer
Terminal Material: Phosphor Bronze
Plating: Sn or Au over 50µ" (1,27µm) Ni
Current Rating: 2A @ 80°C ambient
Operating Temp Range: -55°C to +105°C with Tin; -55°C to +125°C with Gold
Lead-Free Solderable: Yes
RoHS Compliant: Yes



Note: Some lengths, styles and options are non-standard, non-returnable.

FCF - **1** **NO. PINS PER ROW** - **LEAD STYLE** - **PLATING OPTION** - **D** - **CARD SLOT** - **TAIL OPTION** - **SL**

Mates with: EMF

20, 30, 40 & 50
(Call Samtec for other sizes)

Specify LEAD STYLE from chart

-L
= 10µ" (0,25µm) Gold on post, Matte Tin on tail

-S
= 30µ" (0,76µm) Gold on post, Matte Tin on tail

-01
= Accepts (0,80mm) .031" thick card

-RA
= Right Angle
(Leave blank for vertical version. Style -02 only)

| LEAD STYLE | Y | CARD-TO-BOARD SPACE (X) |
|------------|-------------|-------------------------|
| -02 | (6,35) .250 | (2,60) .1025 |
| -03 | (9,53) .375 | (9,53) .375 |

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?EMF

Insulator Material: Black Liquid Crystal Polymer
Contact Material: BeCu
Plating: Au or Sn over 50µ" (1,27µm) Ni
Current Rating: 1A
Operating Temp Range: -55°C to +125°C
Contact Resistance: 10 mΩ max
Insertion Depth: (3,05mm) .120" to (4,06mm) .160"
Insertion Force: (Single contact only) 3.0oz (0,83N) avg.
Withdrawal Force: (Single contact only) 2.0oz (0,56N) avg.
Lead-Free Solderable: Yes
SMT Lead Coplanarity: (0,10mm) .004" max (20) (0,15mm) .006" max (30-50)
RoHS Compliant: Yes



EMF - **1** **NO. PINS PER ROW** - **CARD THICKNESS** - **PLATING OPTION** - **D**

Mates with: FCF

20, 30, 40 & 50
(Call Samtec for other sizes)

-01
= (0,80mm) .031" thick board

-L
= 10µ" (0,25µm) Gold on contact, Matte Tin on tail

-S
= 30µ" (0,76µm) Gold on contact, Matte Tin on tail

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC SILICON VALLEY • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329
 SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 8990337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292 SAMTEC ISRAEL • Tel: 972-3-7526600
 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-61103766 SAMTEC TAIWAN • Tel: 886-2-2735-6109
 Downloaded from Elcodis.com electro SAMTEC HONG KONG • Tel: 852-26009858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9512 7747 SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112