


**Product Details for 1 -213437 -0**



**1 -213437 -0**

[Active](#)

**ARINC 404 Connectors**

[Not ELV or RoHS Compliant](#)

**Product Highlights:**

- ? Sealed
- ? Seal Type = Interface seal on pin insert
- ? Shell Size = 2 Inserts
- ? Shell Configuration = Plug
- ? Contact Arrangement (Module A) = 106

[View all Features](#)

**Quick Links**

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

**Documentation & Additional Information**

**Product Drawings:**

- ? [PLUG CONNECTOR KIT, ARINC 404, DUAL INSERT, RM2P SERIES](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- ? None Available

**Product Specifications:**

- ? None Available

**Application Specifications:**

- ? None Available

**Instruction Sheets:**

- ? None Available

**CAD Files:**

- ? None Available

**Additional Information:**

- ? [Product Line Information](#)

**Related Products:**

- ? [Tooling](#)

[List all Documents](#)

**Product Features** (Please use the Product Drawing for all design activity)

**Product Type Features:**

- ? [Sealed](#) = Yes
- ? [Shell Size](#) = 2 Inserts
- ? Shell Finish = Cadmium plated per QQ -P-416 with yellow chromate conversion.
- ? Comment = Contacts must be ordered separately.

**Mechanical Attachment:**

- ? [Keying](#) = 01

**Electrical Characteristics:**

- ? Shell Configuration = Plug
- ? Signal Contacts = Without
- ? [Shell Mounting Modification](#) = None
- ? [Custom Order Code](#) = 201

**Termination Related Features:**

- ? Seal Type = Interface seal on pin insert

**Contact Related Features:**

- ? Contact Type (Module A) = Pin
- ? Contact Type (Module B) = Pin

**Configuration Related Features:**

- ? [Contact Arrangement \(Module A\)](#) = 106
- ? [Contact Arrangement \(Module B\)](#) = 106

**Industry Standards:**

- ? Government/Industry Qualification = No
- ? [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

**Other:**

- ? Brand = AMP